


FDT459N N-Channel Enhancement Mode Field Effect Transistor

General Description

These N-Channel enhancement mode power field effect transistors are produced using Fairchild's proprietary, high cell density, DMOS technology. This very high density process is especially tailored to minimize on-state resistance, provide superior switching performance. These products are well suited to low voltage, low current applications such as notebook computer power management, battery powered circuits, and DC motor control.

Features

- 6.5 A, 30 V. $R_{DS(ON)} = 0.035\Omega$ @ $V_{GS} = 10$ V
 $R_{DS(ON)} = 0.055 \Omega$ @ $V_{GS} = 4.5$ V.
- High density cell design for extremely low $R_{DS(ON)}$.
- High power and current handling capability in a widely used surface mount package.






Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	FDT459N	Units
V_{DSS}	Drain-Source Voltage	30	V
V_{GSS}	Gate-Source Voltage - Continuous	± 20	V
I_D	Maximum Drain Current - Continuous (Note 1a)	6.5	A
	- Pulsed	20	
P_D	Maximum Power Dissipation (Note 1a)	3	W
	(Note 1b)	1.3	
	(Note 1c)	1.1	
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to 150	°C
THERMAL CHARACTERISTICS			
R_{QJA}	Thermal Resistance, Junction-to-Ambient (Note 1a)	42	°C/W
R_{QJC}	Thermal Resistance, Junction-to-Case (Note 1)	12	°C/W

* Order option J23Z for cropped center drain lead.

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units		
OFF CHARACTERISTICS								
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	30			V		
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	$I_D = 250 \mu\text{A}$, Referenced to 25°C		33		mV/°C		
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 24 \text{ V}, V_{GS} = 0 \text{ V}$ $T_J = 55^\circ\text{C}$		1		μA		
I_{GSSF}	Gate - Body Leakage, Forward	$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$			100	nA		
I_{GSSR}	Gate - Body Leakage, Reverse	$V_{GS} = -20 \text{ V}, V_{DS} = 0 \text{ V}$			-100	nA		
ON CHARACTERISTICS (Note 2)								
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	1	1.6	2	V		
$\Delta V_{GS(\text{th})}/\Delta T_J$	Gate Threshold Voltage Temp.Coefficient	$I_D = 250 \mu\text{A}$, Referenced to 25°C		-4.2		mV/°C		
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS} = 10 \text{ V}, I_D = 6.5 \text{ A}$ $T_J = 125^\circ\text{C}$	0.031	0.035		Ω		
		$V_{GS} = 4.5 \text{ V}, I_D = 5.5 \text{ A}$	0.044	0.06				
$I_{D(\text{ON})}$	On-State Drain Current	$V_{GS} = 10 \text{ V}, V_{DS} = 5 \text{ V}$	20			A		
g_{FS}	Forward Transconductance	$V_{DS} = 10 \text{ V}, I_D = 6.5 \text{ A}$		16		S		
DYNAMIC CHARACTERISTICS								
C_{iss}	Input Capacitance	$V_{DS} = 15 \text{ V}, V_{GS} = 0 \text{ V}, f = 1.0 \text{ MHz}$		365		pF		
C_{oss}	Output Capacitance			210		pF		
C_{rss}	Reverse Transfer Capacitance			70		pF		
SWITCHING CHARACTERISTICS (Note 2)								
$t_{D(\text{on})}$	Turn - On Delay Time	$V_{DD} = 15 \text{ V}, I_D = 1 \text{ A}, V_{GS} = 10 \text{ V}, R_{GEN} = 6 \Omega$		5.2	11	ns		
t_r	Turn - On Rise Time			8.2	16	ns		
$t_{D(\text{off})}$	Turn - Off Delay Time			6	12	ns		
t_f	Turn - Off Fall Time			16	26	ns		
Q_g	Total Gate Charge	$V_{DS} = 10 \text{ V}, I_D = 6.5 \text{ A}, V_{GS} = 10 \text{ V}$		12	17	nC		
Q_{gs}	Gate-Source Charge			2.2		nC		
Q_{gd}	Gate-Drain Charge			3		nC		
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS								
I_s	Maximum Continuous Drain-Source Diode Forward Current				2.5	A		
V_{SD}	Drain-Source Diode Forward Voltage	$V_{GS} = 0 \text{ V}, I_s = 2.5 \text{ A}$ (Note 2)		0.8	1.2	V		
Notes:								
1. R_{jka} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. R_{jca} is guaranteed by design while R_{oca} is determined by the user's board design.								
Typical R_{jka} using the board layouts shown below on FR-4 PCB in a still air environment:								
		a. 42°C/W when mounted on a 1 in^2 pad of 2oz Cu.			b. 95°C/W when mounted on a 0.066 in^2 pad of 2oz Cu.			c. 110°C/W when mounted on a 0.00123 in^2 pad of 2oz Cu.
Scale 1 : 1 on letter size paper								
2. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2.0\%$								

Typical Electrical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Electrical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

Note: Thermal characterization performed using the conditions described in note 1c.
Transient thermal response will change depending on the circuit board design.