



**Microsemi Corp.**  
The diode experts

# 60S SERIES

SCOTTSDALE, AZ

For more information call:  
(602) 941-6300

## DESCRIPTION/FEATURES

- ECONOMICAL 6 AMP  $I_O$  MOLDED DEVICE OFFERS CAPABILITY OF STUD-MOUNTED RECTIFIERS
- 400 AMPS SURGE PROVIDES HIGH IN-RUSH CURRENT CAPABILITY
- WIDE VOLTAGE RANGE AVAILABLE: 50 TO 1000 VOLTS  $V_{RRM}$

## Major Ratings and Characteristics

60S		
$I_F(AV)$	6	A
@ Max. $T_L$	95	$^{\circ}C$
$I_{FSM}$	@ 50 Hz	382
	@ 60 Hz	400
$i^2t$	@ 50 Hz	712
	@ 60 Hz	650
$T_J$	-40 to 175	$^{\circ}C$
$V_{RRM}$ Range	50-1000	V

## VOLTAGE RATINGS

Part Number	Working $V_{RRM}$ (V)	$V_{SR}$ - Max. Direct Reverse Voltage (V)
	$T_J = 40^{\circ}C$ to $200^{\circ}C$	$T_J = 40^{\circ}C$ to $200^{\circ}C$
60S05	50	50
60S1	100	100
60S2	200	200
60S4	400	400
60S5	500	500
60S6	600	600
60S8	800	800
60S10	1000	1000

## ELECTRICAL SPECIFICATIONS


		60S	Units	Conditions
$I_F(AV)$	Max. average forward current	6	A	1 phase operation, 180 $^{\circ}$ conduction, $T_L = 95^{\circ}C$ , $l = 9.5$ mm (0.375 in.)
$I_{FSM}$	Max. peak one-cycle non-repetitive surge current	382	A	Half cycle 50 Hz sine wave or 6 ms rectangular pulse following any rated load condition and with rated $V_{RRM}$ applied.
		400		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
		454		Half cycle 50 Hz sine wave or 6 ms rectangular pulse following any rated load condition and with $V_{RRM}$ applied following surge = 0.
		475		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
$i^2t$	Max. $i^2t$ for fusing	712	$A^2s$	$t = 10$ ms With rated $V_{RRM}$ applied following surge, initial $T_J = 175^{\circ}C$
		650		$t = 8.3$ ms With $V_{RRM} = 0$ following surge, initial $T_J = 175^{\circ}C$
	1006	$t = 10$ ms		
	919	$t = 8.3$ ms		
$i^2\sqrt{t}$	Max. $i^2\sqrt{t}$ for individual device fusing (1)	10 330	$A^2\sqrt{s}$	$t = 0.1$ to 10 ms, $V_{RRM} = 0$ following surge.
$V_{FM}$	Max. peak forward voltage	1.00	V	$I_F(AV) = 6A$ (18.8A peak), $T_J = 25^{\circ}C$
$I_{R(AV)}$	Max. average reverse current	2.0	mA	Max. rated $I_F(AV)$ and $V_{RRM}$ , $T_C = 95^{\circ}C$ , length of leads to the temperature measurement points (heat sinks) = 9.5 mm (0.375 in.)
		1		
		0.8		
		0.5		

## THERMAL-MECHANICAL SPECIFICATIONS

$T_J$	Max. operating junction temperature range	40 to 175	$^{\circ}C$	
$T_{stg}$	Max. storage temperature range	40 to 175	$^{\circ}C$	
$R_{thJC}$	Max. internal thermal resistance, junction-to-leads	-	deg C/W	DC operation, double side cooled, measured 9.5 mm (0.375 in.) from body.
$\rho$	Length of leads (1) (1/8") 3.2 mm	11.0	$\leq 10\%$	
		14.7		
		20.0		
wt	Approximate weight	1.5 (0.053)	g (oz)	

Note (1):  $I^2t$  for time  $t_x = I^2\sqrt{t} - \sqrt{t_x}$

## 6 AMP AXIAL-LEAD SILICON RECTIFIER DIODES



All Dimensions in Inches and (Millimeters)

## MECHANICAL CHARACTERISTICS

CASE: Molded plastic use Flame Retardant Epoxy.


TERMINALS: Axial leads, solderable per MIL-STD-202, Method 208.

POLARITY: Color band denotes cathode.


MOUNTING POSITION: Any.

# 60S Series


## RATING AND CHARACTERISTIC CURVES




**Fig. 1 - Average Forward Current Vs. Lead Temperature at Heat Sinks ( $l = 3/8$  inch)**




**Fig. 2 - Maximum Average Forward Power Loss Vs. Low-Level Average Forward Current**




**Fig. 3 - Maximum Average Forward Power Loss Vs. High-Level Forward Current**



**Fig. 4 - Maximum Instantaneous Forward Voltage Vs. Instantaneous Forward Current**



**Fig. 5 - Maximum Transient Thermal Impedance, Vs. Square Wave Pulse Duration**



**Fig. 6 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses**