

M1254 Surface Mount Crystal

2.5 x 4.0 x 0.75 mm



Features:

- Ultra-Miniature Size
- Tape & Reel
- Leadless Ceramic Package - Seam Sealed
- RoHS Compliant




Applications:

- Handheld Electronic Devices
- PDA, GPS, MP3
- Portable Instruments
- PCMCIA Cards

Ordering Information

Product Series	M1254	6	J	M	XX	00.0000
Operating Temperature	2: -40°C to +85°C	6: -20°C to +70°C				MHz
Tolerance @ +25°C	D: ±10 ppm	E: ±15 ppm	G: ±20 ppm	H: ±25 ppm	J: ±30 ppm (std)	M: ±50 ppm
Stability	D: ±10 ppm	E: ±15 ppm	G: ±20 ppm	H: ±25 ppm	J: ±30 ppm	M: ±50 ppm (std)
Load Capacitance	Blank: 18 pF (std)	S: Series Resonant	XX: Customer Specified 10 pF to 32 pF			
Frequency (customer specified)						



Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions	
Frequency Range	F	12		32	MHz		
Frequency Tolerance	F/F	See Ordering Information			ppm	+25°C	
Frequency Stability	F/F	See Ordering Information			ppm	Over Operating Temperature	
Operating Temperature	T _{opr}	See Ordering Information			°C		
Storage Temperature	T _{stg}	-55		+125	°C		
Aging	F _a			±2	ppm/yr	+25°C	
Load Capacitance	C _L					See Ordering Information	
Shunt Capacitance	C ₀				3	pF	
ESR							
Fundamental AT-Cut Frequencies							
12.000000 to 19.999999 MHz					80	Ohms	All
20.000000 to 25.999999 MHz					70	Ohms	All
26.000000 to 32.000000 MHz					50	Ohms	All
Drive Level	D _L	10	100	300	μW		
Insulation Resistance	I _R	500			Megohms	100 VDC	
Aging	Internal Specification					168 hrs. at +55°C	
Physical Dimensions	MIL-STD-883, Method 2016						
Shock	MIL-STD-202, Method 213 Condition C					100 g	
Vibration	MIL-STD-202, Methods 201 & 204					10 g from 10-2000 Hz	
Thermal Cycle	MIL-STD-883, Method 1010, Condition B					-55°C to +125°C	
Gross Leak	MIL-STD-202, Method 112					30 sec. Immersion	
Fine Leak	MIL-STD-202, Method 112					1 x 10 ⁻⁸ atmcc/sec. min.	
Resistance to Solvents	MIL-STD-883, Method 2015					Three 1 minute soaks	
Maximum Soldering Conditions	MIL-STD-202, Method 210, Condition C					Pb Free = +260°C for 10 secs. max	

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

MtronPTI Lead Free Solder Profile

