



F6908

LINEAR INTEGRATED CIRCUIT


SINGLE-PHASE FULL-WAVE MOTOR DRIVER FOR FAN MOTOR

■ DESCRIPTION

UTC **F6908** is a single-phase full-wave motor driver for fan motor suitable for 5V and 12V operations.

■ FEATURES

- * Soft switching drive for low noise
- * Lock detection and automatic restart function
- * Thermal shut-down protection



*Pb-free plating product number: F6908L


■ PIN DESCRIPTION

PIN NO.	PIN NAME	FUNCTION
1	OUT2	Output 2
2	HO	Hall signal output pin
3	LD	Capacitor terminal for Lock detection, Auto restart
4	V _{CC}	Power supply pin
5	H+	Hall signal input pin +
6	H-	Hall signal input pin -
7	OUT1	Output 1
8	GND	GROUND

■ ORDERING INFORMATION

Order Number		Package	Packing
Normal	Lead Free Plating		
F6908-S08-R	F6908L-S08-R	SOP-8	Tape Reel
F6908-S08-T	F6908L-S08-T	SOP-8	Tube

■ BLOCK DIAGRAM



■ HALL SIGNAL INPUT-OUTPUT TRUTH TABLE

H+	H-	OUT1	OUT2	HO
H	L	H	L	H
L	H	L	H	L

Condition: LD=0V

■ ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V _{CC}	15	V
Output Voltage	V _{OUT}	15	V
Hall Signal Output Voltage	V _{HO}	15	V
Output Current	I _{OUT}	0.7*	A
Hall Signal Output Current	I _{HO}	15	mA
Power Dissipation	P _D	680 **	mW
Operating Temperature	T _{OPR}	-40 ~ +100	°C
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{STG}	-40 ~ +150	°C

* This value is not to be over P_D and ASO.

** To use at temperature above Ta = 25°C reduce 5.5 mW/°C. (On 70.0mm×70.0mm×1.6mm glass epoxy board)

The device is guaranteed to meet performance specification within 0°C ~ 70°C operating temperature range and assured by design from -40°C ~ 100°C, characteristic and correlation with static process control.


■ RECOMMENDED OPERATING CONDITIONS (Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V _{CC}	3 ~ 14	V

■ ELECTRICAL CHARACTERISTICS (Unless otherwise specified Ta = 25°C, V_{CC} = 5V)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Clamp Voltage of Capacitor for Lock Detection	V _{LDCL}		1.14	1.80	2.47	V
Reference Voltage of Capacitor for Lock Detection	V _{LDCP}		0.47	0.76	1.06	V
Output Voltage L	V _{OL}	I _{OUT} =200mA		0.2	0.3	V
Output Voltage H	V _{OH}	I _{OUT} =200mA	3.9	4.1		V
"HO" Terminal Voltage L	V _{HOL}	I _{HO} =5mA		0.3	0.5	V
Supply Current	I _{CC}	At output: OFF	1.5	3.4	8.7	mA
Charge Current of Capacitor for Lock Detection	I _{LDC}	V _{LD} =1.1V	1.50	2.75	4.50	μA
Discharge Current of Capacitor for Lock Detection	I _{LDD}	V _{LD} =1.1V	0.24	0.48	0.90	μA
"HO" Terminal Leak Current	I _{HOL}	V _{HO} =15V		0	50	μA
Charge-Discharge Current Ratio of Capacitor for Lock Detection	R _{CD}	r _{CD} =I _{LDC} /I _{LDD}	4.2	5.7	9.5	
Hall Input Offset Voltage	H _{OFFS}		-10		10	mV
Hall Input-Output Gain	G _{HO}		320	500	680	
Thermal Shutdown				140		°C
TSD Hysteresis	TSD			25		°C

■ POWER DERATING CURVE



To use at temperature above Ta=25°C reduce 5.5mW/°C
(On 70.0mm×70.0mm×1.6mm glass epoxy board)

■ LOCK DETECT CIRCUIT, AUTOMATIC RESTART CIRCUIT

Charge and discharge time at motor lock condition varies with the value of external capacitor at LD terminal, and is given by the following equation.

$$T_{ON} \text{ (Charge time)} = \frac{C \times (V_{LDCL} - V_{LDCLP})}{I_{LDC}}$$

$$T_{OFF} \text{ (Discharge time)} = \frac{C \times (V_{LDCL} - V_{LDCLP})}{I_{LDD}}$$

C: Capacitor at LD pin

The following value shows charge time and discharge time at C=0.47µF for reference.

Charge time = 0.18S (Output: ON)

Discharge time = 1.02S (Output: OFF)

■ SHOWS TIMING CHART OF LD PIN




Fig.1 Timing chart (LD terminal, HO terminal)

■ CAUTIONS

(1) Power dissipation

IC power dissipation varies widely with supply voltage, output current and application of IC. Please pay attention not to exceed the allowable power rating.

(2) Hall signal input terminals (H+, H-)




Fig.2 Hall amp input bias voltage range

A. Hall signal amplitude should be key within range $0V \sim V_{CC}-2V$.

B. The output signal of this IC is the amplified by about 500 times of hall input signal coith pattern shown below for different level ok signal input.




Fig.3 Difference of output signal depending on hall input signal

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.