

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI MLN1027F** is Designed for Class A, Linear Applications up to 1.0 GHz.

FEATURES:

- Class A Operation
- $P_G = 12$ dB at 0.5 W/1.0 GHz
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	300 mA
V_{CE}	20 V
P_{DISS}	--- W
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +200 °C
θ_{JC}	25 °C/W

PACKAGE STYLE .250 2L FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.028 / 0.71	.032 / 0.81
B	.740 / 18.80	
C	.245 / 6.22	.255 / 6.48
D	.128 / 3.25	.132 / 3.35
E	.125 / 3.18	
F	.110 / 2.79	.117 / 2.97
G	.117 / 2.97	
H	.560 / 14.22	.570 / 14.48
I	.790 / 20.07	.810 / 20.57
J	.225 / 5.72	.235 / 5.97
K	.165 / 4.19	.185 / 4.70
L	.003 / 0.08	.007 / 0.18
M	.058 / 1.47	.068 / 1.73
N	.119 / 3.02	.135 / 3.43
P	.149 / 3.78	.187 / 4.75

ORDER CODE: ASI10618

CHARACTERISTICS $T_C = 25$ °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 1.0$ mA	50			V
BV_{CEO}	$I_C = 5.0$ mA	20			V
BV_{EBO}	$I_E = 1.0$ mA	3.5			V
I_{CEO}	$V_{CE} = 18$ V			0.5	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 100$ mA	15		120	---
C_{OB}	$V_{CB} = 28$ V $f = 1.0$ MHz			3.5	pF
P_G	$V_{CE} = 20$ V $P_{OUT} = 0.5$ W $f = 1.0$ GHz $I_{CQ} = 100$ mA	12			dB