


**Features**

- High Reliability
- High Conductance
- For General Purpose Switching Applications

**Mechanical Data**

- Case: MiniMELF, Glass
- Terminals: Solderable per MIL-STD-202, Method 208
- Marking: Cathode Band Only
- Polarity: Cathode Band
- Weight: 0.05 grams (approx.)



MiniMELF		
Dim	Min	Max
A	3.30	3.70
B	1.30	1.60
C	0.28	0.50
All Dimensions in mm		

**Maximum Ratings @ T<sub>A</sub> = 25°C unless otherwise specified**

Characteristic	Symbol	LL4454	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	75	V
Working Peak Reverse Voltage	V <sub>RWM</sub>		
DC Blocking Voltage	V <sub>R</sub>		
Forward Continuous Current (Note 1)	I <sub>FM</sub>	300	mA
Average Rectified Output Current (Note 1)	I <sub>O</sub>	150	mA
Non-Repetitive Peak Forward Surge Current @ t ≤ 1.0s @ t = 1.0μs	I <sub>FSM</sub>	1.0 2.0	A
Power Dissipation (Note 1)	P <sub>d</sub>	400	mW
Thermal Resistance, Junction to Ambient Air (Note 1)	R <sub>θJA</sub>	300	K/W
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>STG</sub>	-65 to +175	°C

**Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified**

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Maximum Forward Voltage Drop	V <sub>FM</sub>	—	—	1.0	V	I <sub>F</sub> = 10mA
Maximum Peak Reverse Current	I <sub>RM</sub>	—	—	100	nA	V <sub>R</sub> = 50V
Junction Capacitance	C <sub>j</sub>	—	4.0	—	pF	V <sub>R</sub> = 0V, f = 1.0MHz
Reverse Recovery Time	t <sub>rr</sub>	—	4.0	—	ns	I <sub>F</sub> = I <sub>R</sub> = 10mA, I <sub>tr</sub> = 1.0 x I <sub>R</sub> , R <sub>L</sub> = 100Ω

Note: 1. Valid provided that electrodes are kept at ambient temperature.