

Description

This device is power factor correction controller using a discontinues conduction mode of boost converter. Especially, it is optimized for electronic ballasts which prevent abnormal functions in load runaway and feedback loop fault conditions and low power and high density power supplies which require minimum board size. The external component R/C filter is not necessary because the R/C filter is included in current sense block. This is the improved version with a pin out equivalent to world standard.

Features

- Dynamic, Static & Feedback OVP
- Extremely Low Start up Current (30uA Typ.)
- Very Low Operating Current (4mA Typ.)
- Internal Self Start Timer
- Current Sense with Internal RC Filter
- Trimmed $\pm 1.5\%$ internal Reference
- Under Voltage Lock Out with Hysteresis
- Pin Compatible to World Standard
- High Current Totem Pole Gate Drive

Applications


- Electronic Ballast
- SMPS

Ordering Information

Type NO.	Marking	Package Code
S6500P	S6500P	DIP-8

Outline Dimensions

unit : mm



Electrical Characteristics

V_{cc}=12V, -25°C ≤ T_a ≤ 125°C, unless otherwise specified.

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
SUPPLY VOLTAGE & CURRENT SECTION						
Start Threshold Voltage	V _{th(st)}	V _{cc} Increasing	9.5	10.5	11.5	V
UVLO Hysteresis	HY(st)	-	1.5	2.5	3.5	V
Start up Supply Current	I _{st}	V _{cc} =9V	5	30	50	uA
Operating Supply Current	I _{cc}	Output not switching	-	3	6	mA
Operating Current at OVP	I _{occ}	INV=3V	-	1.6	2.5	mA
Dynamic Operating Supply Current	I _{dcc}	50kHz, C _l =1nF	-	4	8	mA
Maximum Supply Voltage	V _{cc(max)}	I _{cc} =30mA	17	18	19	V
ERROR AMPLIFIER SECTION						
Voltage Feedback Input Threshold	V _{ref}	I _{ref} =0mA, T _a =25°C	2.465	2.5	2.535	V
Line Regulation (note 1)	△V _{ref1}	12V ≤ V _{cc} ≤ 17V	-	0.1	10	mV
Temperature Stability of V _{ref} (note 1)	△V _{ref2}	Temp= -25°C to 85°C	-	20	-	mV
Input Bias Current (Pin1)	I _{b(ea)}	-	-0.5	-	0.5	uA
Output Source Current	I _{source}	INV=2V, V _{m2} =4V	-2	-5	-	mA
Output Sink Current	I _{sink}	INV=3V, V _{m2} =4V	3	6	-	mA
Lower Clamp Voltage	V _{low}	INV=3V	1.9	2	2.1	V
MULTIPLIER SECTION						
Input Bias Current (Pin3)	I _{b(m)}	-	-0.5	-	0.5	uA
M1 Input Voltage Range (pin3) (note2)	△V _{m1}	Range From 0V	4	4.5	-	V
M2 Input Voltage Range (pin2) (note2)	△V _{m2}	Range From V _{ref}	V _{ref} +25	V _{ref} +3	-	V
Multiplier Gain (note 3)	K	V _m =1V, V _{m2} =4V	0.45	0.6	0.75	1/V
Maximum Multiplier Output Voltage	V _{mo(max)}	INV=1V, V _{m1} =4V	1.8	2	2.2	V

Electrical Characteristics

V_{cc}=12V, -25 °C ≤ T_a ≤ 125 °C, unless otherwise specified.

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
CURRENT SENSE COMPARATOR						
Input Offset Voltage	V _{io(cs)}	V _{m1} =0V, V _{m2} =2.3V	0	10	25	mV
Input Bias Current (Pin4)	I _{b(cs)}	0V ≤ V _{cs} ≤ 1.8V	-0.5	-	.05	uA
Current Sense Delay to Output (note2)	t _{d(cs)}	-	-	200	500	ns
ZERO CURRENT DETECTOR						
Input Voltage Threshold	V _{th(det)}	V _{det} Increasing	1.7	2	2.3	V
Detect Hysteresis	HY(det)	-	0.2	0.5	0.8	V
Input Low Clamp Voltage	V _{clamp(l)}	I _{det} =-3mA	0.4	0.8	1.2	V
Input High Clamp Voltage	V _{clamp(h)}	I _{det} =3mA	6	7.5	9	V
Input Bias Current (Pin5)	I _{b(det)}	1V ≤ V _{det} ≤ 5V	-1	-0.1	1	uA
Input High/Low Clamp Diode Current (note 2)	I _{clamp}	-	-	-	±3	mA
OUTPUT SECTION						
Output Voltage High	V _{oh}	I _o =10mA	8.5	10	-	V
Output Voltage Low	V _{ol}	I _o =10mA	-	1.5	2	V
Rising Time (note2)	t _r	C _l =1nF	-	120	200	nS
Falling Time (note2)	t _f	C _l =1nF	-	50	120	nS
Output Voltage with UVLO Activated	V _{o(uvlo)}	V _{cc} =5V, I _o =50uA	-	-	1	V
SELF STARTER SECTION						
Self Start Time Delay (note2)	t _{d(ss)}	V _{m1} =1V, V _{m2} =3.5V	-	150	-	us
OVER VOLTAGE PROTECTION SECTION						
Feedback OVP Threshold Voltage	V _{th(f)}	-	0.3	0.4	0.5	V
Dynamic OVP Detecting Current	I _{ovp(d)}	-	35	40	45	uA
Static OVP Threshold Voltage	V _{th(s)}	-	2.15	2.3	2.45	V

Note : 1) Because the reference is not brought out externally, this specification can't be tested on the package

Part. It is guaranteed by design.

2) This parameter, although guaranteed, is not tested in production.

3) Multiplier gain $K = V_{mo} / (V_{m1} \times (V_{m2} - v_{ref}))$

Electrical Characteristic Curves

Fig. 1 Supply Voltage vs. Supply Current




Fig. 2 Supply Voltage vs. Startup Current




Fig. 3 Temperature vs. Voltage Feedback Input Threshold




Fig. 4 Supply Voltage vs. Operating Supply Current




Fig. 5 Supply Voltage vs. Operating Current at OVP





Fig. 6 Maximum Supply Voltage vs. Supply Current



Electrical Characteristic Curves

Fig. 7 Idet Input Voltage vs. Output Voltage




Fig. 8 Multiplier Input Voltage vs. CS Threshold Voltage




Fig. 9 Idet Input Voltage vs. Input Low Clamp Voltage





Fig.10 Idet Input Voltage vs. Input High Clamp Voltage



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.