


X00134

SFT815 HIGH ENERGY FAST SWITCHING NPN POWER TRANSISTOR 90 AMPS, 300 VOLT	SSDI 14849 FIRESTONE BLVD. LA MIRADA, CA. 90638 TEL (213) 921-9660 FAX (213) 921-2396
---	--

CASE STYLE
JEDEC TO-3 WITH .060 PINS



FEATURES

- ▶ HIGH ENERGY
- ▶ FAST SWITCHING - tr 300 nsec MAX
- ▶ SINGLE CHIP CONSTRUCTION
- ▶ VERY LOW SATURATION
- ▶ HIGH GAIN TO 90 AMPS
- ▶ SUPERIOR PERFORMANCE TO
SDT96301-SDT96303
- ▶ EUTECTIC DIE ATTACH
- ▶ HI-REL CONSTRUCTION

MAXIMUM RATINGS

RATING	SYMBOL	VALUE	UNIT
Collector-Emitter Voltage	VCEO	140	Volts
Collector-Base Voltage	VCBO	300	Volts
Emitter-Base Voltage	VEBO	10	Volts
Collector Current	IC	90	Amps
Base Current	IB	15	Amps
Total Device Dissipation @ Tc = 50 °C Derate Above 50 °C	PD	300 2	Watts W/ °C
Operating and Storage Temperature	TJ, Tstg	-65 to +200	°C

THERMAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	VALUE	UNIT
Thermal Resistance, Junction to Case	RθJC	0.5	°C/W

ELECTRICAL CHARACTERISTICS


Characteristics	Symbol	Min	Max	Unit
Collector-Emitter Breakdown Voltage* (IC = 200mAdc)	BVCEO	140		Volts
Collector-Base Breakdown Voltage (IC = 100uAdc)	BVCBO	300		Volts

ELECTRICAL CHARACTERISTICS

Characteristics		Symbol	Min	Max	Unit
Emitter-Base Breakdown Voltage ($I_E = 100 \mu\text{A}$)		BVEBO	10	-	Vdc
Collector Cutoff Current ($V_{CB} = 200\text{Vdc}$)		ICBO	-	10	μA
Emitter Cutoff Current ($V_{EB} = 8\text{Vdc}$)		IEBO	-	10	μA
DC Current Gain* ($I_C = 30\text{A}$, $V_{CE} = 5\text{Vdc}$) ($I_C = 50\text{A}$, $V_{CE} = 5\text{Vdc}$) ($I_C = 90\text{A}$, $V_{CE} = 5\text{Vdc}$)		hFE	35 25 15	- - -	
Collector-Emitter Saturation Voltage* ($I_C = 30\text{A}$, $I_B = 3\text{A}$) ($I_C = 50\text{A}$, $I_B = 5\text{A}$) ($I_C = 90\text{A}$, $I_B = 9\text{A}$)		VCE(SAT)	- - -	1.0 1.2 1.8	Vdc
Base-Emitter Saturation Voltage* ($I_C = 30\text{A}$, $I_B = 3\text{A}$) ($I_C = 50\text{A}$, $I_B = 5\text{A}$) ($I_C = 90\text{A}$, $I_B = 9\text{A}$)		VBE(SAT)	- - -	1.2 1.6 2.0	Vdc
Current Gain Bandwidth Product ($I_C = 1\text{A}$, $V_{CE} = 10\text{Vdc}$, $f = 1\text{MHz}$)		fT	10	-	MHz
Output Capacitance ($V_{CB} = 10\text{Vdc}$, $I_E = 0\text{A}$, $f = 1\text{MHz}$)		Cob	-	800	pf
Second Breakdown Collector Current ($t = 1\text{sec}$, non repetitive, $V_{CE} = 30\text{V}$)		IS/B	2		A
Delay Time	VCC = 100V, IC = 50A IB1 = IB2 = 1A VBB = -5V	td	-	0.1	μs
Rise Time		tr	-	0.3	μs
Storage Time		ts	-	1.8	μs
Fall Time		tf	-	0.3	μs

*Pulse Test: Pulse Width = 300 μs , Duty Cycle = 2%

PHYSICAL DIMENSIONS



SSDI

SOLID STATE DEVICES, INC.

14849 FIRESTONE BOULEVARD, LA MIRADA, CA 90638
Telephone (213) 921-9660 ♦ FAX (213) 921-2396