

### Features

- Glass Passivated Junction Protection for Superior Blocking Voltage and Stability
- 2000V Capability
- Low Forward Voltage Drop

### Applications

- Bridge Rectifiers
- Power Modules
- Motor Controls

### Electrical Ratings

Part Number	Description	$I_{T(AV)}$ ①	$V_{TM}$ @ $I_T$ ②	$V_{DRM} / V_{RRM}$ ③ (V)	$I_{TSM}$ (10ms)	
CCR28H-10/20	Diode, Die, 25A	25	1.25	35	1000 -2000	850
CCR34H-10/20	Diode, Die, 60A	60	1.25	90	1000 -2000	2000
CCR44H-10/20	Diode, Die, 100A	100	1.25	140	1000 -2000	3000
CCR50H-10/20	Diode, Die, 150A	150	1.25	210	1000 -2000	4000
CCR58H-10/20	Diode, Die, 185A	185	1.25	250	1000 -2000	4500

①  $T_j = 150^\circ\text{C}$ ,  $T_c = 80^\circ\text{C}$ . Rated values depend on assembly materials and conditions. Assemblies must be void-free and have sufficient heat sinking to achieve maximum ratings.

② 25°C

③ Part number suffix, 10=1000V, 12=1200V, 16=1600V, 20=2000V


### Part Numbering

Examples:

Series Voltage  
CCR34H -12=1200V

#### General Note:

Metallization - CR:Ni:Ag  
Aluminum Metallization Available - Contact Factory



#### Dimensions in inches

Series Type	A	B	C	D	Thickness
CCR28H	0.180	0.180	0.140	0.140	0.011 Fig. 1
CCR34H	0.230	0.230	0.190	0.190	0.011 Fig. 1
CCR44H	0.339	0.339	0.299	0.299	0.011 Fig. 1
CCR50H	0.400	0.400	0.370	0.370	0.011 Fig. 1
CCR58H	0.478	0.478	0.422	0.422	0.011 Fig. 1

#### Dimensions in mm

Series Type	A	B	C	D	Thickness
CCR28H	4.572	4.572	3.556	3.556	0.275 Fig. 1
CCR34H	5.842	5.842	4.826	4.826	0.275 Fig. 1
CCR44H	8.611	8.611	7.595	7.595	0.275 Fig. 1
CCR50H	10.160	10.160	9.398	9.398	0.275 Fig. 1
CCR58H	12.141	12.141	10.719	10.719	0.275 Fig. 1

iso9001 CERTIFIED

**USA**  
Sales & Tech Support (866) 258-5057  
Email: sales@cynergy3.com

Cynergy3 Components  
2320 Paseo de las Americas, Suite 104  
San Diego, CA 92154

www.cynergy3.com

**EUROPE - UK**  
Telephone +44 (0) 1202 897969  
Fax +44 (0) 1202 891918

Email: sales@cynergy3.com  
Cynergy3 Components Ltd.  
7 Cobham Road  
Ferndown Industrial Estate  
Wimborne, Dorset BH21 7PE

**ASIA - Thailand**  
Telephone +66 (0)2 665 2517  
Fax +66 (0)2 665 2588

Cynergy 3 Components, Asia  
18/8 Fico Place 12th Floor  
Soi Sukhumvit 21 (Asoke)  
Klongtoey Nua, Wattana  
Bangkok, Thailand 10110