

Silicon NPN Power Transistors

2SD665

DESCRIPTION


- With TO-3 package
- Complement to type 2SB645
- High power dissipation

APPLICATIONS

- Power amplifier applications
- Power switching applications
- DC-DC converters

PINNING(see Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector

Absolute maximum ratings($T_a =$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	200	V
V_{CEO}	Collector-emitter voltage	Open base	200	V
V_{EBO}	Emitter-base voltage	Open collector	5	V
I_C	Collector current		15	A
I_B	Base current		4	A
P_C	Collector power dissipation	$T_C=25$	150	W
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

Silicon NPN Power Transistors

2SD665

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =25mA ; I _B =0	200			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =10A; I _B =1A			2.0	V
V _{BEsat}	Base-emitter saturation voltage	I _C =10A; I _B =1A			2.5	V
I _{CBO}	Collector cut-off current	V _{CB} =200V; I _E =0			0.1	mA
I _{EBO}	Emitter cut-off current	V _{EB} =5V; I _C =0			0.1	mA
h _{FE}	DC current gain	I _C =1A ; V _{CE} =5V	40		140	
C _{OB}	Output capacitance	I _E =0 ; V _{CB} =10V; f=1.0MHz		300		pF
f _T	Transition frequency	I _C =1A ; V _{CE} =5V		15		MHz

◆ h_{FE} Classifications

O	R
40-80	70-140

PACKAGE OUTLINE

