

## Safety Connection Systems

### Safety Wired Distribution Box, 8-Port, Dual-Channel (2 N.C.) plus Individual N.O. Enunciation




#### Specifications

Body	Red PBT
Connector Insert	PBT
Receptacle Shell	Nickel-plated brass
Contacts	Gold-plated palladium/nickel
Cable	Oil resistant yellow PVC jacket, (14) 18AWG conductors
Cable O.D.	9.8mm (0.39in)
Enclosure Rating	IP67, NEMA 6P
Temperature	-20°C to +105°C (-13°F to +221°F)

#### Features

- Prewired for dual-channel N.C. safety plus individual N.O. enunciation
- Eight 6-pin AC micro connectors
- 14-conductor main cable
- Individual enunciation outputs or each port
- For use in category 2 or 3 systems per EN 954-1

#### Product Selection

Face View of Female (8)	Number of Ports	Illuminated	Rating	Face View of Male (1)	Cable Length—m (ft)	Catalogue Number
	8	LEDs	10-30V DC	Cable	5 (16.4)	898R-P68MT-A5
					10 (32.8)	898R-P68MT-A10
Shorting Plug for unused ports						898R-61MU-RM
Patchcord, straight to straight DC Micro, ⊗ = length in meters 1, 2, 3, 5, 10 standard						889R-F6ECRM-⊗

#### Approximate Dimensions—mm (inches)

See 8-port dimensions on page 15-5.

#### Wiring Diagrams

