


FEATURES

- 14.00-14.50 GHz Bandwidth
- Input/Output Impedance Matched to 50 Ohms
- +41.0 dBm Output Power at 1dB Compression
- 6.0 dB Power Gain at 1dB Compression
- 23% Power Added Efficiency
- Hermetic Metal Flange Package
- 100% Tested for DC, RF, and R_{TH}



ELECTRICAL CHARACTERISTICS (T_a = 25°C)



Caution! ESD sensitive device.

SYMBOL	PARAMETERS/TEST CONDITIONS ¹	MIN	TYP	MAX	UNITS
P _{1dB}	Output Power at 1dB Compression f = 14.00-14.50GHz V _{DS} = 10 V, I _{DSQ} ≈ 3200mA	40.0	41.0		dBm
G _{1dB}	Gain at 1dB Compression f = 14.00-14.50GHz V _{DS} = 10 V, I _{DSQ} ≈ 3200mA	5.0	6.0		dB
ΔG	Gain Flatness f = 14.00-14.50GHz V _{DS} = 10 V, I _{DSQ} ≈ 3200mA			±0.6	dB
PAE	Power Added Efficiency at 1dB Compression V _{DS} = 10 V, I _{DSQ} ≈ 3200mA f = 14.00-14.50GHz		23		%
I _{d1dB}	Drain Current at 1dB Compression f = 14.00-14.50GHz		3960	5100	mA
I _{DSS}	Saturated Drain Current V _{DS} = 3 V, V _{GS} = 0 V		5900	8200	mA
V _P	Pinch-off Voltage V _{DS} = 3 V, I _{DS} = 64 mA		-1.2	-2.5	V
R _{TH}	Thermal Resistance ²		2.5	3.5	°C/W

Notes:

1. Tested with 50 Ohm gate resistor.
2. Overall R_{th} depends on case mounting.

ABSOLUTE MAXIMUM RATINGS FOR CONTINUOUS OPERATION^{1,2}

SYMBOL	CHARACTERISTIC	VALUE
V _{DS}	Drain to Source Voltage	10 V
V _{GS}	Gate to Source Voltage	-4.5 V
I _{DS}	Drain Current	I _{DSS}
I _{GSF}	Forward Gate Current	220 mA
P _{IN}	Input Power	@ 3dB compression
P _T	Total Power Dissipation	35 W
T _{CH}	Channel Temperature	150°C
T _{STG}	Storage Temperature	-65/+150°C

- Notes:
1. Exceeding any of the above ratings may result in permanent damage.
 2. Exceeding any of the above ratings may reduce MTTF below design goals.

Specifications are subject to change without notice.



EID1414A1-12

UPDATED 07/12/2007

14.00-14.50 GHz 12-Watt Internally Matched Power FET

DISCLAIMER

EXCELICS SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. EXCELICS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN.

LIFE SUPPORT POLICY

EXCELICS SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF EXCELICS SEMICONDUCTOR, INC. AS HERE IN:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness

Specifications are subject to change without notice.

Excelics Semiconductor, Inc. 310 De Guigne Drive, Sunnyvale, CA 94085
Phone: 408-737-1711 Fax: 408-737-1868 Web: www.excelics.com

page 2 of 2
Revised July 2007