

Surface Mount Schottky Barrier Rectifier

Features

- Low Profile in SMA Package
- Low power loss, high efficiency
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications



SMA

Mechanical Data

Case:	SMA Package, Molded plastic body
Terminals:	Solder plated, solderable per MIL-STD-750, Method 2026
Polarity	Color band denotes the cathode end

Maximum Ratings ($T_{Ambient}=25^{\circ}C$ unless noted otherwise)

Symbols	Description	SS22A	SS23A	SS24A	SS25A	SS26A	Unit
VRMS	Maximum RMS voltage	14	21	28	35	42	V
VRRM	Maximum repetitive peak reverse voltage	20	30	40	50	60	V
VDC	Maximum DC blocking voltage	20	30	40	50	60	V
I(AV)	Maximum average forward rectified current at T_L (SEE FIG.1)	2.0					A
IFSM	Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	50.0					A
RθJA RθJL	Maximum thermal resistance (NOTE 2)	75 17					$^{\circ}C/W$ $^{\circ}C/W$
TJ	Operating junction temperature range	-65 to +125			-65 to +150		$^{\circ}C$
TSTG	Storage Temperature Range	-65 to +150					$^{\circ}C$

Electrical Characteristics ($T_{Ambient}=25^{\circ}C$ unless noted otherwise)

Symbols	Description	SS22A	SS23A	SS24A	SS25A	SS26A	Unit
VF	Maximum instantaneous forward voltage at 2.0A (NOTE 1)	0.50			0.70		V
IR	Maximum DC reverse current (NOTE 1) $T_A=25^{\circ}C$ at rated DC blocking voltage $T_A=100^{\circ}C$	0.4 10.0					mA

NOTES:

- (1) Pulse test: 300us pulse width, 1% duty cycle
- (2) P.C.B. mounted with 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas

Surface Mount Schottky Barrier Rectifier

SS22A - SS26A

Typical Characteristics Curves

Fig.1- Forward Current Derating Curve




Fig.2- Maximum Non-repetitive Peak Forward Surge Current




Fig.3- Typical Instantaneous Forward Characteristics




Fig.4- Typical Reverse Current Characteristics






Fig.5-Typical junction capacitance



Surface Mount Schottky Barrier Rectifier

SS22A - SS26A

Dimensions in inches (mm)



How to contact us

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 247-2232 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931