



Kaga Electronics(USA) Inc.

ADAPTER - 65W

Green Mode

Meet CEC Regulations & RoHS Compliance



FEATURE

Desktop	IEC 320/C6,C8,C14
Input range	90-264V/47~63Hz
Output	12V~24V/2.7A~5A(65W max.)
Efficiency	85% typical
Protection	Short circuit protection/Over voltage protection
Load regulation	±5%
Leakage current	Less than 3.5mA(3Pins),0.25mA(2Pin)
M.T.B.F.	50,000 hours min. at 25°C, full load
Dimension	115X53X37

APPLICATION

LCD Monitor, Notebook, Printer, Portable device

SAFETY & EMI

Safety	UL/cUL/GS/CB/PSE/BSMI
EMI	CE Class B; Conduction & Radiation MEET

ENVIRONMENTAL

Operating temperature	0~+40°C
Storage Temperature	-20~+60°C
Relative Humidity	(operating)20~80%RH (storage)10~90%RH

MODEL

NO	MODEL NAME	Voltage(V)	Current(A)	Power(W)
1	STD-1250P	12	5	60
2	STD-1543P	15	4.3	65
3	STD-1640P	16	4	64
4	STD-1836P	18	3.6	65
5	STD-1934P	19	3.4	65
6	STD-2032P	20	3.25	65
7	STD-2427P	24	2.7	65

MECHANICAL DRAWING

