



Kaga Electronics(USA) Inc.

ADAPTER - 50W

Green Mode

Meet CEC Regulations & RoHS Compliance



FEATURE

Desktop	IEC 320/C6,C8,C14
Input range	90~264V/47~63 HZ
Output	9V~24V/2.1A~5A(50W max.)
Efficiency	80% Typical, 85% for CEC Requirement
Protection	Short Circuit Protection/Over Voltage Protection
Load Regulation	±5%
Leakage Current	Less than 3.5mA(3Pin), 0.25mA(2 Pin)
M.T.B.F	50000 hours min. at 25°C., full load
Dimension	115(L) x 53(W) x 37(H) mm

SAFETY & EMI

SAFTY	UL/cUL/GS/CB/PSE/BSMI
EMI	CE/FCC Class B, Conduction & Raditaton MEET

ENVIRONMENTAL

Operating Temperature	0~ +40°C
Storage Temperature	- 20~ + 60°C
Relative Humidly	(operating) 20~80% RH (storage)10~90%RH

APPLICATION

LCD Monitor , Notebook , Printer , Portable device

MODEL

NO	MODEL NAME	Voltage(V)	Current(A)	Power(W)
1	STD-0905P	9	5.0	45
2	STD-1242P	12	4.2	50
3	STD-1533P	15	3.3	50
4	STD-1827P	18	2.7	49
5	STD-1926P	19	2.6	49
6	STD-2025P	20	2.5	50
7	STD-2421P	24	2.1	50
8	STD-4810P	48	1.0	50

MECHANICAL DRAWING

