



VRLA Rechargeable Battery

EB50-12 (EB50-12FR)



FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high power & high cyclic usage
- Low self-discharge rate, lower than 3% capacity loss per month

APPLICATION

- UPS
- E-bike
- Wheelchairs
- Lawn Mowers
- Golf-Carts
- Electrical Scooter



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	50Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	16500g(36.38lbs.)
Terminals	I2 (M6 Female thread)
Internal Resistance	≤6mΩ (Fully Charged)
Max. Discharge Current	750 A (5 sec.)
Max. Charge Current	15 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)


ISO 9001	
ISO14001	
UL	
CE	
<ul style="list-style-type: none"> ● IEC61056 ● JIS C 8702 ● GB/T 19639 	

DIMENSION(mm/inch)


OUTER DIMENSIONS

TERMINAL TYPE

- **Length**
197±1.5 (7.76±0.06)
- **Width**
165±1.5 (6.50±0.06)
- **Container Height**
171±1.5 (6.73±0.06)
- **Total Height**
171±1.5 (6.73±0.06)



- Terminal I2



Terminal Hardware Initial Torque: I2(5.5Nm±5%)

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	1346.7	1090.5	685.9	543.8	415.0	228.0	175.0	110.9	56.14	29.36
1.75V	1459.0	1141.7	712.2	563.5	427.0	234.0	178.3	112.3	57.00	30.00
1.70V	1511.7	1176.2	727.8	574.8	434.5	236.4	180.0	113.2	57.29	30.14
1.65V	1547.8	1203.7	738.4	582.8	440.5	238.8	181.7	114.0	57.43	30.21
1.60V	1578.5	1227.4	745.9	588.7	445.0	240.0	182.5	114.0	57.43	30.21
1.50V	1610.2	1251.9	753.4	594.6	449.7	241.2	183.6	114.0	57.43	30.21

Constant power discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	118.5	94.8	58.1	45.9	34.9	19.0	14.6	9.24	4.68	2.45
1.75V	128.4	99.3	60.4	47.6	35.9	19.5	14.9	9.36	4.75	2.50
1.70V	133.1	102.3	61.7	48.5	36.5	19.7	15.0	9.43	4.77	2.51
1.65V	136.3	104.7	62.6	49.2	37.0	19.9	15.1	9.50	4.79	2.52
1.60V	139.0	106.7	63.2	49.7	37.4	20.0	15.2	9.50	4.79	2.52
1.50V	141.7	108.9	63.8	50.2	37.8	20.1	15.3	9.50	4.79	2.52

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.
A/0 REV. Jul. 2009

Powered by **B.B. Battery Co., Ltd.**