



- NOTE:
1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
  2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 7.5V Vop(typ.), 5V VDD
  3. VIEWING DIR.: 6:00
  4. OP. TEMP.:  $-20^{\circ}C \sim 70^{\circ}C$
  5. ST. TEMP.:  $-40^{\circ}C \sim 80^{\circ}C$
  7. BACKLIGHT: LED(Orange), Vf=5.0V, If<150mA 500cd/m<sup>2</sup>

Wavelength 625±5nm

TOLERANCE
>0~6 ±0.10
>6~80 ±0.20
>80~240 ±0.30
>240~400 ±0.50
// L ⊙ ±0.10

		<b>HTDISPLAY CO., LTD.</b>	
DESIGN	LI JINTANG	06.06.23	STANDARD
CHECKED			TECHNOLOGY
APPROVED			Q.A
DRAWING No. : HG1223206C-YF62L-VA		REV. : A	
DRAWING TITLE: LCD MODULE		SCALE : -	
FILE NO. : 8		UNIT : MM	
		SHEET : 1/2	

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.18