


ADSL LINE TRANSFORMERS



- For use with Alcatel's DynaMiTe MTK-20140 ADSL chipset
- Excellent THD performance
- Small footprint

Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

Part Number	Application	Mounting	Turns Ratio (± 2%) (1-4):(10-7)	OCL @ 10 KHz, 0.1 V (1-4) with (2-3) shorted	Leakage Inductance @ 300 KHz, 0.1 V (1-4) with (2-3), (7-10) and (8-9) shorted	Longitudinal Balance (from 30 KHz to 1.1 MHz)
B2068	CO	THT	2:1 (Line to Chip)	410 µH (± 10%)	6.5 µH MAX	-40 dB MIN
B2064 ²	CPE	SMT	1:1 (Line to Chip)	480 µH (± 10%)	10.0 µH MAX	-40 dB MIN

Additional Specifications


Part Number	THD (Linearity - Typical)	DC Resistance (1-4)/(w/2-3 shorted)	Isolation Voltage (Vrms)	Insertion Loss ¹ (@ 100 KHz and 1.1 MHz)
B2068	-72 dB MIN @ 20 KHz	0.6 Ω MAX	1500	<1.0 dB
B2064 ²	-72 dB MIN @ 10 KHz	1.0 Ω MAX	1500	<1.0 dB

¹ Frequency Response: ±0.5 dB MAX, from 100 KHz to 1.1 MHz.; -1.5 dB MAX from 30 KHz to 100 KHz

² Transformers are shipped in tubes unless tape and reel is specified. Please add the suffix "T" (i.e. B2064T) for tape and reel orders.

Mechanics

B2068




Weight 6.2 grams

Tray60/tray


Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are ± $\frac{.010}{0,25}$

B2064



Schematic



For More Information :

UNITED STATES (Worldwide)

12220 World Trade Drive
San Diego, CA 92128
Quick-Facts: 619 674 9672
http://www.pulseeng.com
TEL: 858 674 8100
FAX: 858 674 8262

UNITED KINGDOM (Northern Europe)

1 & 2 Huxley Road
The Surrey Research Park
Guildford, Surrey GU2 5RE
United Kingdom
TEL: 44 1483 401700
FAX: 44 1483 401701

FRANCE (Southern Europe)

Zone Industrielle
F-39270
Orgelet
France
TEL: 33 3 84 35 04 04
FAX: 33 3 84 25 46 41

SINGAPORE (Southern Asia)

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324
TEL: 65 287 8998
FAX: 65 280 0080

TAIWAN, R.O.C. (Northern Asia)

3F-4, No. 81, Sec. 1
HsinTai Wu Road
Hsi-Chih, Taipei Hsien
Taiwan, R.O.C.
Tel: 886 2 2698 0228
FAX: 886 2 2698 0948

DISTRIBUTOR

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.