


IEC Appliance Outlet H, Screw-on Mounting, Solder Terminal

new

**Description**

Connector,
- Pin temperature 70 °C, Protection class II, Cable

References

[General Product Information](#)

Weblinks

[Approvals, RoHS, CHINA-RoHS, Mating Connectors, e-Store, Distributor-Stock-Check, Accessories](#)

Technical Data

Ratings IEC	10A / 250VAC; 50Hz
Ratings UL/CSA	10A / 250VAC; 60Hz
Dielectric Strength	> 2 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	Cable
Panel Thickness s	Screw max 0Nm Snap-in 1 mm
Material: Housing	black, UL 94V-0

Config. Code

Product Configurator

5099 - H - A B C 0 - D - E J

The characters are placeholders for the correspondingly keys of selections from the key tables.

5099 - H - A B C 0 - D - E J = Type

Type	Configuration key
protection class 2	B

5099 - H - A B C 0 - D - E J = Terminals

Terminal L	Configuration key
solder terminal 	1

5099 - H - A B C 0 - D - E J = Terminals

Terminal N	Configuration key
solder terminal	1

Symbols similar as in table A

5099 - H - A B C 0 - D - E J = Terminals

Terminal Ground	Configuration key
without terminal	0

Symbols similar as in table A

5099 - H - A B C 0 - D - E J = Color

Color	Configuration key
jet black; RAL9005	A
standard color: black	

5099 - H - A B C 0 - D - E J = Style

Style	Configuration key
insert type	5

5099 - H - A B C 0 - D - E J = Condition

Condition	Configuration key
not concerning this product	nv

Mating Inlets/Plugs

Category / Description



[Interconnection Cord Overview complete](#)

Interconnection Cord with IEC Plug G, Angled	607B
Interconnection Cord with IEC Plug G, Angled	608B
Interconnection Cord with IEC Plug G, Straight	609B

[Interconnection Cord further types to 5099](#)