



General ordering data

Order No.	9457900250
Part designation	SAIL-M12WM12W-5-2.5U
EAN	4032248229246
Qty.	1 pc(s).

Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-30 °C
Cable diameter, max.	5.8 mm
Cable diameter, min	5.4 mm
Connection cross-section	0,34
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M12
Core cross-section	0.34 mm ²
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	125 V
Sheathing colour	black
jumpered	No
No. of poles	5
Version	pin, 90° - socket 90°

Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

Similar products

Order No.	Part designation	Version
9457900150	SAIL-M12WM12W-5-1.5U	Sensor/Actuator line, Connecting line, LED: No, 1.50 m, PUR/PVC
9457901000	SAIL-M12WM12W-5-10U	Sensor/Actuator line, Connecting line, LED: No, 10.00 m, PUR/PVC
9457900200	SAIL-M12WM12W-5-2.0U	Sensor/Actuator line, Connecting line, LED: No, 2.00 m, PUR/PVC
9457900300	SAIL-M12WM12W-5-3.0U	Sensor/Actuator line, Connecting line, LED: No, 3.00 m, PUR/PVC
9457900500	SAIL-M12WM12W-5-5.0U	Sensor/Actuator line, Connecting line, LED: No, 5.00 m, PUR/PVC
9457900060	SAIL-M12WM12W-5-0.6U	
9457900120	SAIL-M12WM12W-5-1.2U	Sensor/Actuator line, Connecting line, LED: No, 1.20 m, PUR/PVC
9457900600	SAIL-M12WM12W-5-6.0U	Sensor/Actuator line, Connecting line, LED: No, 6.00 m, PUR/PVC