


## OptiMOS™ Small-Signal-Transistor

### Features

- N-Channel
- Enhancement mode
- Avalanche rated
- Logic Level
- dv/dt rated

### Product Summary

Drain source voltage	$V_{DS}$	55	V
Drain-source on-state resistance	$R_{DS(on)}$	33	mΩ
Continuous drain current	$I_D$	5.2	A



Type	Package	Ordering Code	Marking	Pin 1	PIN 2/4	PIN 3
BSP603S2L	SOT-223	-	-	G	D	S

### Maximum Ratings, at $T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_A = 25\text{ °C}$ $T_A = 70\text{ °C}$	$I_D$	5.2 4.1	A
Pulsed drain current $T_A = 25\text{ °C}$	$I_{D\text{ puls}}$	21	
Avalanche energy, single pulse $I_D = 5.2\text{ A}$ , $V_{DD} = 25\text{ V}$ , $R_{GS} = 25\text{ Ω}$	$E_{AS}$	150	mJ
Avalanche energy, periodic limited by $T_{jmax}$	$E_{AR}$	0.18	
Reverse diode dv/dt $I_S = 5.2\text{ A}$ , $V_{DS} = 40\text{ V}$ , $di/dt = 200\text{ A/μs}$ , $T_{jmax} = 150\text{ °C}$	dv/dt	6	kV/μs
Gate source voltage	$V_{GS}$	± 20	V
Power dissipation $T_A = 25\text{ °C}$	$P_{tot}$	1.8	W
Operating and storage temperature	$T_j, T_{stg}$	-55...+150	°C
IEC climatic category; DIN IEC 68-1		55/150/56	

**Thermal Characteristics**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Characteristics</b>					
Thermal resistance, junction - soldering point (Pin 3)	$R_{thJS}$	-	17	tbd	K/W
SMD version, device on PCB: @ min. footprint	$R_{thJA}$	-	100	tbd	
@ 6 cm <sup>2</sup> cooling area F)		-	-	70	

**Electrical Characteristics**, at  $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Static Characteristics</b>					
Drain-source breakdown voltage $V_{GS} = 0\text{ V}$ , $I_D = 1\text{ mA}$	$V_{(BR)DSS}$	55	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D = 50\text{ }\mu\text{A}$	$V_{GS(th)}$	1.2	1.6	2	
Zero gate voltage drain current $V_{DS} = 55\text{ V}$ , $V_{GS} = 0\text{ V}$ , $T_j = 25\text{ }^\circ\text{C}$ $V_{DS} = 55\text{ V}$ , $V_{GS} = 0\text{ V}$ , $T_j = 125\text{ }^\circ\text{C}$	$I_{DSS}$	-	0.1	1	$\mu\text{A}$
Gate-source leakage current $V_{GS} = 20\text{ V}$ , $V_{DS} = 0\text{ V}$	$I_{GSS}$	-	10	100	
Drain-source on-state resistance $V_{GS} = 4.5\text{ V}$ , $I_D = 2.6\text{ A}$	$R_{DS(on)}$	-	tbd	40	$\text{m}\Omega$
Drain-source on-state resistance $V_{GS} = 10\text{ V}$ , $I_D = 2.6\text{ A}$	$R_{DS(on)}$	-	tbd	33	

Electrical Characteristics, at  $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
<b>Dynamic Characteristics</b>						
Transconductance	$g_{fs}$	$V_{DS} \geq 2 \cdot I_D \cdot R_{DS(on)max}$ , $I_D = 4.1$	tbd	tbd	-	S
Input capacitance	$C_{iss}$	$V_{GS} = 0V, V_{DS} = 25V,$ $f = 1MHz$	-	tbd	tbd	pF
Output capacitance	$C_{oss}$		-	tbd	tbd	
Reverse transfer capacitance	$C_{rss}$		-	tbd	tbd	
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 30V, V_{GS} = 4.5V,$ $I_D = 5.2A, R_G = 5.6\Omega$	-	tbd	tbd	ns
Rise time	$t_r$		-	tbd	tbd	
Turn-off delay time	$t_{d(off)}$		-	tbd	tbd	
Fall time	$t_f$		-	tbd	tbd	

Gate Charge Characteristics

Gate to source charge	$Q_{gs}$	$V_{DD} = 40V, I_D = 5.2A$	-	tbd	tbd	nC
Gate to drain charge	$Q_{gd}$		-	tbd	tbd	
Gate charge total	$Q_g$	$V_{DD} = 40V, I_D = 5.2A,$ $V_{GS} = 0 \text{ to } 10V$	-	tbd	tbd	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD} = 40V, I_D = 5.2A$	-	tbd	-	V

Reverse Diode

Inverse diode continuous forward current	$I_S$	$T_A = 25^\circ\text{C}$	-	-	5.2	A
Inverse diode direct current, pulsed	$I_{SM}$		-	-	21	
Inverse diode forward voltage	$V_{SD}$	$V_{GS} = 0V, I_F = 5.2A$	-	tbd	tbd	V
Reverse recovery time	$t_{rr}$	$V_R = 30V, I_F = I_S,$ $di_F/dt = 100A/\mu s$	-	tbd	tbd	ns
Reverse recovery charge	$Q_{rr}$		-	tbd	tbd	nC
Soft factor $t_f / t_s$	S		-	tbd	-	



**Published by**

**Infineon Technologies AG,  
Bereichs Kommunikation  
St.-Martin-Strasse 53,  
D-81541 München  
© Infineon Technologies AG 1999  
All Rights Reserved.**

**Attention please!**

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

**Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

**Warnings**

Due to technical requirements components may contain dangerous substances.  
For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.