




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-2 @20°C	2.000 ohms max.
D.C. RESISTANCE	3-4 @20°C	0.270 ohms max.
D.C. RESISTANCE	5-8 @20°C	0.026 ohms max.
INDUCTANCE	1-2 10kHz, 100mVAC, Ls	2.500mH ±10%
SATURATION CURRENT	1-2 2.000mH min.	480mA
LEAKAGE INDUCTANCE	1-2 tie(3+4+5+8), 10kHz, 100mVAC, Ls	40.00uH max.
DIELECTRIC	1-8 tie(2+3), 4500VAC, 1 second	-
URNS RATIO	(2-1):(4-3)	16.67:1, ±2%
URNS RATIO	(2-1):(8-5)	12.5:1, ±2%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: <b>Tape &amp; Reel</b> PKG-0813 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1°      Decimals: ±.005 [.13] Fractions: ±1/64      Footprint: ±.003 [.08]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>760875142</b>
6A	6/11	SEE REVISION SHEET FOR REVISION LEVEL	CONVENTION PLACEMENT	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 760875142	SPECIFICATION SHEET 1 OF 1