

6

5

4

3

2

1

MATERIAL AND FINISH:

Insulator: Impact resistance Polypropylene, black,

UL-94V-HB rated

PDSN-11-1A (wire leads): PVC, 26 AWG

Contact & terminals:





PDSN-11-1C: Brass, Nickel plated

Spring: Spring Steel, Nickel plated imbedded in Polypropylene


ENVIRONMENTAL:

Operating temperature: -5°C to +83°C

RoHS
COMPLIANT



PDSN-11-1A WIRE LEADS



PDSN-11-1C SOLDER LUGS

REV	DATE	CHANGE	CHKG	CHKD	APPR

TOLERANCE UNLESS OTHERWISE SPECIFIED		
X	±	1
X.X	±	0.4
X.XX	±	0.20
DRAWN BY	GQ	DATE: 05/24/02
CHECK BY	TD	DATE: 05/30/02
APPR BY	PB	DATE: 05/30/02

Power Dynamics, Inc.

Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: 1 CELL TYPE "D" BATTERY HOLDER

PDSN-11-1X		SHEET 1 of 1
PART #:	SIZE: A	ALL DIMENSIONS FOR REFERENCE ONLY DIMENSIONS ARE IN MILLIMETERS
SCALE: NTS	REV:	

6

5

4

3

2

1