

SPECIAL APPLICATION WIREWOUND RESISTOR VISHAY TYPE

WSL0805-9 WSL1206-9, WSL2010-9, WSL2512-9



DESCRIPTION: WSL TYPE ZERO OHM JUMPER

This is a standard WSL0805, WSL1206, WSL2010, WSL2512 resistor designed to be used as a zero ohm jumper.

- * All copper construction with solderable terminations.
- * Encapsulated with a high temperature coating.




Pb-free
Available



RoHS*
COMPLIANT

DIMENSIONAL OUTLINE:



All physical dimensions are the same as standard 0.01Ω WSL type resistor.

SPECIFICATIONS:

RESISTANCE VALUE:	0.0003Ω MAX	
TEMPERATURE COEFFICIENT:	3900 PPM/°C	
MAXIMUM CONTINUOUS CURRENT:	WSL2512-9	81 AMPS
	WSL2010-9	58 AMPS
	WSL1206-9	41 AMPS
	WSL0805-9	29 AMPS
OPERATING TEMPERATURE:	-65°C TO +170°C	

GLOBAL PART NUMBER INFORMATION				
Global Part Numbering: WSL120600000ZEA9				
W	S	L	1	2
0	6	0	0	0
0	0	0	0	0
Z	E	A	9	
GLOBAL MODEL	RESISTANCE VALUE	TOLERANCE CODE	PACKAGING CODE	SPECIAL
WSL0805 WSL1206 WSL2010 WSL2512	00000 For Jumper	Z For Jumper	EA = Lead Free, Tape/Reel EK = Lead Free, Bulk TA = Pb Tape/Reel (R86) BA = Pb Bulk (B43)	(Dash number) 9 for Jumper

*Pb containing terminations are not RoHS compliant, exemptions may apply

For technical questions, contact ww2bresistors@vishay.com

VISHAY DALE ELECTRONICS
P.O. BOX 609 / Columbus, NE 68602-0609
Phone: (402) 564-3131