


PIFR2501~2506 N/ P



INSULATE PRESS-FIT




Features

- Low Cost
- Super Cool
- Long life Features
- High Current Capability

NOTE:

- **1. PILFR25XXP Positive (Forward) (+)**
Cathode To Case, Color Code Red
- **2. PILFR25XXN Negative (Reverse) (-)**
Anode To Case, Color Code Black
- 3. Lead have 1mm, 1.3mm And 2.5mm

Electrical Characteristics@25C	Symbol	PIFR2501P PIFR2501N	PIFR2502P PIFR2502N	PIFR2504P PIFR2504N	PIFR2506P PIFR2506N	Unit
Average Forward Current, I _o at T _c =150C 60HZ, Resistive Or Inductive Load	IF	25				A(DC)
Peak Reverse Voltage, Repetitive:VRRM	VRRM	100	200	400	600	V(DC)
DC Reverse Voltage, VR	V(DC)	100	200	400	600	
Maximum RMS Voltage	VRMS	70	140	280	420	
Max. Inst Forward Voltage Drop. VF at 100Amp	VF	1.2				V
Peak Forward Surge Current, IFM(surge): 8.3ms. Single Half Sine-Wave Superimposed On Rated Load (JEDEC method)	IFSM	400				A
Maximum Reverse Current IR At Rated DC Reverse Voltage. TC= 25C	IR	10				uA
Maximum Reverse Current IR At Rated DC Reverse Voltage. TC=100C	IR	500				uA
Maximum Thermal Resistance, Junction To Case (single side cooled)	R _{θJA}	0.8				C/W
Operating And Storage Temperature Range	T _j ; T _{strg}	-65 to +175				C



Ratings at 25 Deg. C ambient temperature unless otherwise specified.

Single Phase Half Wave, 60 Hz Resistive or Inductive Load.

For Capacitive Load, Derate Current by 20%.

- NOTES:**
1. Measured @ 1 MHz and applied reverse voltage of 4.0V.
 2. Thermal Resistance Junction to Ambient, Jedec Method.
 3. When Mounted to heat sink, from body.