


PASTERNAK ENTERPRISES RG62A/U



IMPEDANCE: 93 OHMS
INNER CONDUCTOR DIAMETER: .0253"
INNER CONDUCTOR MATERIAL: COPPER CLAD STEEL
DIELECTRIC DIAMETER: .146"
DIELECTRIC MATERIAL: AIR-SPACE SOLID POLYETHYLENE
NUMBER OF SHIELDS: 1
SHIELD MATERIAL: BARE COPPER
OUTER DIAMETER: .239"
BRAID COVERAGE: 95%
JACKET MATERIAL: BLACK POLYVINYLCHLORIDE, NON CONTAMINATING
NOMINAL CAPACITANCE (pf/ft): 13.5

NOMINAL ATTENUATION (PER 100 FEET)

10 MHz	.90 dB
100 MHz	2.70 dB
1 GHz	8.70 dB



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

RG62A/U

DES. 93 OHM COAXIAL CABLE

REV. B

FSCM NO. 53919

CAD FILE 121912

SCALE N/A

SIZE A

2233

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.