



Home > Search Tools > Part Number

## Part Number Search

You Searched For:  Go

**Note:** Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

- [Sales Support](#)
- [Product Overview](#)
- [Stock Check](#)
- [Product Home](#)

Our Catalog Part Number: RMDM-21SHY11M2  
 Brand: Cannon Product Category: Micro Product Line: Micros Series: MICRO



CONSULT FACTORY

RoHS compliant = material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2002/95/EC

CONSULT FACTORY

RoHS compatible = Compatible with lead free soldering process

[Download Datasheet](#)

Product Datasheet

- Series
- Arrangement
- Gender
- Contact Material
- Contact Typ
- Contact Resistance
- Termination Type
- Shell Material
- Shell Finish
- Insulator Material
- Hardware
- Coupling
- Current Rating
- Dielectric Withstanding Voltage
- Insulator Resistance
- Thermal Shock
- Physical Shock
- Vibration
- Durability
- Moisture Resistance
- SaltSpray

RoHS - Micro "D" Metal Shell  
 21 Contact  
 Socket  
 gold plated copper alloy  
 crimp  
 8 milliohms max.  
 30" Min, M22759/11 #26AWG, White  
 RoHS - Aluminum  
 Nickel  
 RoHS - contact size 9 to100 = liquid crystalline polymer, contact arrangements 7C2 or 24C4 = Diallyl phthalate  
 Allen head jackscrew assembly, low profile  
 Jackscrew Coupling  
 3 A max.  
 600 VAC at sea level  
 150 VAC at 70,00' altitude  
 5000 megohms min.  
 -55°/+125°  
 50 G's, 3 axes, 6 milisecond duration sawtooth pulse  
 20G's, 10-2000 Hz. 12 hours  
 500 cycles of mating and unmating, 500 CPH max.  
 Insulator resistance > 100 megohms  
 48 hours

Specifications and dimensions subject to change.

