


UL SP MINI-COM® MINI-JACK™ Category 5e Module

- Termination cap provides excellent strain relief, helps control cable bend radius and securely retains wires in place
- Clear, removable termination cap provides easy troubleshooting
- Patented termination style ensures twists are maintained to within 1/2" (12.7mm), per TIA/EIA installation requirements
- Orange module base designates Category 5e performance


- Can be re-terminated a minimum of 10 times
- Terminates 24 and 22 AWG solid unshielded twisted pair cable
- IDC contact design eliminates need to strip individual conductors
- Universal (accepts 2, 3 or 4-pair modular plugs without damage)
- Can be clearly identified with labels found on page E11-E12




Part Number	Description	No. of Module Spaces	Color†	Std. Pkg. Qty.	Std. Ctn. Qty.
Universal 8 Position, 8 Wire T568A and T568B Coded					
CJ588IW	8 position, 8 wire universal module. Termination cap is color coded for T568A and T568B wiring schemes.	1	Off White	1	50
CJS588	8 position, 8 wire universal module. Termination cap is color coded for T568A and T568B wiring schemes with one piece shield.	1	Off White	1	50

†Other colors available. See page A3.
Also works with modular patch panels found on pages C8-C10.

UL SP MINI-COM MINI-JACK Category 5e Module with Micro-Cap



Accommodates large and/or unique shaped cable



Right angle exit in shallow installation spaces

Part Number	Description	No. of Module Spaces	T568 Wire Scheme	Color†	Std. Pkg. Qty.	Std. Ctn. Qty.
CJ588SAIW	8 position, 8 wire universal module. Termination cap is color coded for wiring schemes. Cap designed for large and/or unique shaped cables and for shallow installation spaces.	1	A	Off White	1	50
CJ588SBIW	8 position, 8 wire universal module. Termination cap is color coded for wiring schemes. Cap designed for large and/or unique shaped cables and for shallow installation spaces.	1	B	Off White	1	50


†Other colors available. See page A3.

UL SP MINI-COM MINI-JACK Category 3 Modules

- Terminates 24 and 22 AWG solid unshielded twisted pair cable
- White jack base designates Category 3 performance
- Can be clearly identified with labels found on page E11-E12
- Can be clearly identified with icons found on page B14

Part Number	Description	No. of Module Spaces	Color†	Std. Pkg. Qty.	Std. Ctn. Qty.
Universal 8 Position, 8 Wire T568A and T568B Coded					
CJ88IW	8 position, 8 wire universal module. Termination cap is color coded for T568A and T568B wiring schemes.	1	Off White	1	50
6 Position, 3-Pair USOC Coded					
CJ66UIW	6 position, 4 wire module. Termination cap is color coded for USOC wiring scheme.	1	Off White	1	50
6 Position, 6 Wire					
CJ66IW	6 position, 6 wire module.	1	Off White	1	50
6 Position, 4 Wire					
CJ64IW	6 position, 4 wire module.	1	Off White	1	50

†Other colors available. See page A3.



CJ88



CJ66U



CJ66



CJ64