





Vinyl Insulated Straight Blade Terminals

Cat. No.	Wire Range	Ins. Color	Dimensions				Standard Bagged Qty.		
			B	F		A		T	I.D.
			(mm)	(in.)					
TV18-10BL	22-16	Red	.091	10	.394	.819	.030	.157	50
TV18-18BL	22-16	Red	.087	18	.709	1.134	.030	.157	50
TV14-10BL	16-14	Blue	.094	10	.394	.819	.031	.177	50
TV14-18BL	16-14	Blue	.087	18	.709	1.134	.031	.177	50
TV10-10BL	12-10	Yellow	.110	10	.394	.906	.039	.252	25





Vinyl Insulated Straight Pin Terminals

Cat. No.	Wire Range	Ins. Color	F		B Dia.	A	I.D.	Standard Bagged Qty.
			(mm)	(in.)				
TV18-12PT	22-16	Red	12	.472	.075	.898	.157	50
TV14-12PT	16-14	Blue	12	.472	.075	.898	.177	50
TV10-14PT	12-10	Yellow	14	.551	.110	1.063	.252	25




Nylon Wire Joints

Cat. No.	Wire Range		Dimensions				Standard Bagged Qty.
	Min.	Max.	D	A	I.D.	F	
TN18-WJ	4 #22	3 #18	.197	.713	.106	.276	50
TN14-WJ	2 #16	2 #14	.220	.827	.130	.276	50
TN10-WJ	2 #12	1 #10	.280	1.004	.173	.295	25



Multiple Quick Splices

Cat. No.	Wire Range	Ins. Color	Dimensions		Standard Bagged Qty.
			W	A	
TV18-00QS	22-18 AWG	Red	.787	1.063	25
TV14-00QS	16-14 AWG	Blue	.787	1.063	25
TV10-00QS	12-10 AWG	Yellow	.807	1.358	10



Type of Connector