


# Fixed-DIP Delay Lines

SERIES: 2211

$$T_D/T_R = 10/1$$



## Specifications:

- Standard 24 pins DIP.
- TTL and DTL compatible.
- $T_d/T_r = 10/1$
- Delay tolerance:  $\pm 5\%$  or 1 ns whichever is greater.
- Temperature coefficient: 100 PPM/ $^{\circ}$ C.
- Temperature range:  $-55^{\circ}$ C to  $+125^{\circ}$ C.
- Dielectric breakdown: 50 Vdc.
- Meets or exceeds MIL-D-23859C.
- Epoxy encapsulated.

Part No.	Impedance ( $\Omega$ )	Total Delay (ns)	Rdc ( $\Omega$ )
2211-50A	50	50	3.2
2211-60A	50	60	3.5
2211-80A	50	80	5.0
2211-100A	50	100	6.0
2211-150A	50	150	6.0
2211-50B	100	50	6.0
2211-60B	100	60	6.0
2211-80B	100	80	6.5
2211-100B	100	100	7.0
2211-150B	100	150	8.0
2211-200B	100	200	8.5
2211-300B	100	300	11.0
2211-400B	100	400	12.0
2211-40C	200	40	7.0
2211-80C	200	80	8.0
2211-120C	200	120	10.0
2211-200C	200	200	13.0
2211-300C	200	300	12.0
2211-400C	200	400	15.0
2211-500C	200	500	17.0
2211-600C	200	600	23.0
2211-50D	250	50	7.0
2211-100D	250	100	10.0
2211-150D	250	150	12.0
2211-180D	250	180	14.0
2211-200D	250	200	22.0
2211-250D	250	250	21.0
2211-300D	250	300	23.0
2211-380D	250	380	25.0
2211-400D	250	400	26.0
2211-500D	250	500	30.0
2211-600D	250	600	37.0
2211-750D	250	750	40.0
2211-200G	500	200	20.0
2211-300G	500	300	37.0
2211-400G	500	400	40.0
2211-500G	500	500	45.0
2211-600G	500	600	52.0
2211-800G	500	800	80.0
2211-1000G	500	1000	100.0
2211-1200G	500	1200	110.0
2211-1500G	500	1500	130.0
2211-2000G	500	2000	156.0

