






Specifications

Number of Poles	4 +G 5
Termination Method	Crimp
Contacts	Stamped & Rolled, 2.5 mm Copper Alloy, Silver Plated
Rated Current	16A
Rated Voltage	600V
Rated Impulse Voltage	8.0 kV
Test Voltage	5.7 kV
Volume Resistance	≤5 milliohms



Tools			
	Crimping Tool		CT700TB
	Crimping Die	20 – 16 AWG 16 – 14 AWG	CD730TB CD740TB
	Contact Locator	20 – 16 AWG 16 – 14 AWG	CL010TB CL020TB
	Contact Removal Tool		RT800TB
	Insert Puller		PT300TB

Dummy Inserts		0
	Male Blind Insert: for Frame place keeping	MC100M
	Female Blind Insert: for Frame place keeping	FC000M



Inserts

Pin & Sleeve

4 & 5 Position


Crimp Terminal Inserts		4P +G
	Male Insert	MC704M
	Female Insert	FC604M

**Ground Makes First, Breaks Last*


Crimp Terminal Inserts		5P
	Male Insert	MC705M
	Female Insert	FC605M

Contacts

Male Crimp Pins

	0.5 – 1.5 mm ²	20 – 16 AWG	MP16RF16
	1.5 – 2.5 mm ²	16 – 14 AWG	MP14RF16
	2.5 – 4 mm ²	12 AWG	MP12RF16

Female Crimp Pins

	0.5 – 1.5 mm ²	20 – 16 AWG	FP16RF16
	1.5 – 2.5 mm ²	16 – 14 AWG	FP14RF16
	2.5 – 4 mm ²	12 AWG	FP12RF16