





CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



TERM. NO.'s FOR REF. ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	5-3 @20°C	0.085 ohms ±10%
D.C. RESISTANCE	6-10 @20°C	0.025 ohms ±10%
D.C. RESISTANCE	2-1 @20°C	0.155 ohms ±10%
INDUCTANCE	5-3 100kHz, 100mVAC, Ls	38.00uH ±10%
6C SATURATION CURRENT	20% rolloff from initial	3.5ADC
6B LEAKAGE INDUCTANCE	5-3 tie(1+2, 6+10), 100kHz, 100mVAC, Ls	470nH max.
DIELECTRIC	5-6 tie(3+2), 1875VAC, 1 second	1500VAC, 1 minute
DIELECTRIC	2-3 625VAC, 1 second	500VAC, 1 minute
TURNS RATIO	(5-3):(6-10)	2:1, ±1%
TURNS RATIO	(5-3):(2-1)	1.82:1, ±1%

- 6C GENERAL SPECIFICATIONS:  
 OPERATING TEMPERATURE RANGE: -40°C to +125°C.  
 AMBIENT TEMPERATURE RANGE: -40°C to +75°C.

REV.	DATE	Packaging Specifications Method: <b>Tape &amp; Reel</b> PKG-0499 www.midcom-inc.com		Tolerances unless otherwise specified: Angles: ±1°      Decimals: ±.005 [.13] Fractions: ±1/64      Footprint: ±.005 [.13]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>750310742</b>
6C	1/09					
6B	8/08			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750310742	
6A	7/08	SEE REVISION SHEET FOR REVISION LEVEL				

