

# RF AMPLIFIER

Available as: WNMP1024, 8 Pin .625" Sq. Surface Mount - Gullwing  
 BXMP1024, SMA Connectorized Housing

## MODEL *BXMP1024*

Preliminary

### Features

- High Output Power: +33.0 dBm Typical
- High Third Order Intercept: +45 dBm Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

### Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point ..... +60 dBm (Typ.)  
 Second Order Two Tone Intercept Point ..... +54 dBm (Typ.)  
 Third Order Two Tone Intercept Point ..... +45 dBm (Typ.)

### Specifications


CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	100 - 500 MHz	100 - 500 MHz
Gain (dB)	23.0	22.0 Min.
Power @ 1 dB Comp. (dBm)	+33.0	+32.5 Min.
Reverse Isolation (dB)	-17.0	-16.0 Max.
VSWR In	1.8:1	2.2:1 Max.
Out	1.8:1	2.1:1 Max.
Noise figure (dB)	5.5	6.5 Max.
Power Vdc	+15	+15
mA	500	550 Max.

### Maximum (No Damage) Ratings

Ambient Operating Temperature ..... -55°C to + 100 °C  
 Storage Temperature ..... -62°C to + 125 °C  
 Case Temperature ..... + 125 °C  
 DC Voltage ..... + 18 Volts  
 Continuous RF Input Power ..... + 20 dBm  
 Short Term RF Input Power .... 500 Milliwatts (1 Minute Max.)  
 Maximum Peak Power ..... 0.5 Watt (3 μsec Max.)

Note: Care should always be taken to effectively ground the case of each unit.

### Typical Performance Data



Legend ——— + 25 °C    - - - - + 85 °C    ······ -55 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 03/29/06

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001