

Part Number: C1802

Revision Level: 11/19/2012

**2C 14 AWG (105/34) OFHC BC PP, PVC**
**COMMAND® SERIES**
**A. CONSTRUCTION**

Conductor:	14 AWG 105/34 BC	<b><u>DIAMETERS</u></b>
Insulation:	.009" Wall, Polypropylene (PP)	.074" nom
Cable Core:	2C @ 6.00" LHL	.092" nom
Jacket:	.030" Polyvinyl Chloride (PVC)	.184" nom
Print Legend:	<b>CAROL ® -- C1802 -- COMMAND OFHC HD 14AWG 2C ROHS -- 75C E60233-8 (UL)                  CL3 -- LL69381 CSA AWM I/II A/B 80C 600V FT4 -- MADE IN USA                  (Date code) (Seq Footage)</b>	

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

**C. ELECTRICAL PROPERTIES**

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	2.62 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	23.8pF/ft @ 1kHz (nom)

**D. COLOR CODE**

Item	COLOR
1	BLACK
2	RED

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_