



①



18RAD-187
vinyl insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M

187 Series – Male Tabs

Cat. No.	Pkg. Qty.	Tab Size	Wire Range	Max Ins.	Wt./Lbs. Per 1000	Dia. A
① 18RAD-187	100	.187 x .032	22-18	.150	4	.87
18RAD-188	100	.187 x .020	22-18	.150	4	.87
14RBD-187	100	.187 x .032	16-14	.170	4	.87
14RBD-188	100	.187 x .020	16-14	.170	4	.87

U.L. Listed E66716

Material: brass

Finish: tin plated



②



RA18-111F
nylon-insulated
installing tool –
WT465


110 Series – Disconnects *

Cat. No.	Pkg. Qty.	Tab Size	Wire Range	Max Ins.	Wt./Lbs. Per 1000	Dimensions	
						A	B
② RA18-110F	100	.110 x .032	22-18	.110	4	.75	.15
RA10	1000	.110 x .032	22-18	.110	4	.75	.15
RA18-111F	100	.110 x .020	22-18	.110	4	.75	.15
RA11	1000	.110 x .020	22-18	.110	4	.75	.15
RB14-110F	100	.110 x .032	16-14	.135	4	.75	.15
RB10	1000	.110 x .032	16-14	.135	4	.75	.15
RB14-111F	100	.110 x .020	16-14	.135	4	.75	.15
RB11	1000	.110 x .020	16-14	.135	4	.75	.15
③ A18-110F	100	.110 x .020	22-18	–	3	.59	.15
A10	1000	.110 x .020	22-18	–	3	.59	.15
A18-111F	100	.110 x .020	22-18	–	3	.59	.15
A11	1000	.110 x .020	22-18	–	3	.59	.15
B14-110F	100	.110 x .032	16-14	–	3	.59	.15
B10	1000	.110 x .032	16-14	–	3	.59	.15
B14-111F	100	.110 x .020	16-14	–	3	.59	.15
B11	1000	.110 x .020	16-14	–	3	.59	.15

*Not U.L. Listed

Material: brass

Finish: tin plated



③



A18-111F
non-insulated
installing tools –
WT111M, WT2000,
WT112M

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See page 57. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)