


Silicon Carbide Power Schottky Diode Chip

Features

- 1200 V Schottky rectifier
- 250 °C maximum operating temperature
- Temperature independent switching behavior
- Superior surge current capability
- Positive temperature coefficient of V_F
- Extremely fast switching speeds
- Superior figure of merit Q_C/I_F



Maximum Ratings at $T_j = 250\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Repetitive peak reverse voltage	V_{RRM}		1200	V
Continuous forward current	I_F	$T_C \leq 235\text{ °C}$	1	A
RMS forward current	$I_{F(RMS)}$	$T_C \leq 235\text{ °C}$	2	A
Operating and storage temperature	T_j, T_{stg}		-55 to 250	°C

Electrical Characteristics at $T_j = 250\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Diode forward voltage	V_F	$I_F = 1\text{ A}, T_j = 25\text{ °C}$		1.96		V
		$I_F = 1\text{ A}, T_j = 210\text{ °C}$		3.1		
Reverse current	I_R	$V_R = 1200\text{ V}, T_j = 25\text{ °C}$		0.1	10	μA
		$V_R = 1200\text{ V}, T_j = 275\text{ °C}$		6.6	30	
Total capacitive charge	Q_C	$I_F \leq I_{F,MAX}$ $di_F/dt = 200\text{ A}/\mu\text{s}$ $T_j = 210\text{ °C}$	$V_R = 400\text{ V}$	6		nC
	$V_R = 960\text{ V}$		11			
Switching time	t_s	$V_R = 400\text{ V}$ $V_R = 960\text{ V}$		< 17		ns
Total capacitance	C		$V_R = 1\text{ V}, f = 1\text{ MHz}, T_j = 25\text{ °C}$		66	
		$V_R = 400\text{ V}, f = 1\text{ MHz}, T_j = 25\text{ °C}$		10		
		$V_R = 1000\text{ V}, f = 1\text{ MHz}, T_j = 25\text{ °C}$		8		

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	Assuming TO-276 package	3.55	°C/W
-------------------------------------	------------	-------------------------	------	------

*For chip size and metallization, please refer to the mechanical datasheet (must have a non-disclosure agreement with GeneSiC Semiconductor).




Figure 1: Typical Forward Characteristics




Figure 2: Typical Reverse Characteristics




Figure 3: Typical Junction Capacitance vs Reverse Voltage Characteristics




Figure 4: Typical Switching Energy vs Reverse Voltage Characteristics

Revision History			
Date	Revision	Comments	Supersedes
2012/04/03	0	Initial release	

Published by
 GeneSiC Semiconductor, Inc.
 43670 Trade Center Place Suite 155
 Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

SPICE Model Parameters

Copy the following code into a SPICE software program for simulation of the GB01SHT12-CAL device.

```
*      MODEL OF GeneSiC Semiconductor Inc.
*
*      $Revision:   1.0           $
*      $Date:      05-SEP-2013   $
*
*      GeneSiC Semiconductor Inc.
*      43670 Trade Center Place Ste. 155
*      Dulles, VA 20166
*      http://www.genesicsemi.com/index.php/sic-products/schottky
*
*      COPYRIGHT (C) 2013 GeneSiC Semiconductor Inc.
*      ALL RIGHTS RESERVED
*
*      These models are provided "AS IS, WHERE IS, AND WITH NO WARRANTY
*      OF ANY KIND EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED
*      TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
*      PARTICULAR PURPOSE."
*      Models accurate up to 2 times rated drain current.
*
*      Start of GB01SHT12-CAL SPICE Model
*
.SUBCKT GB01SHT12 ANODE KATHODE
R1 ANODE INT R=((TEMP-24)*0.0099); Temperature Dependant Resistor
D1 INT KATHODE GB01SHT12_25C; Call the 25C Diode Model
D2 ANODE KATHODE GB01SHT12_PIN; Call the PiN Diode Model
.MODEL GB01SHT12_25C D
+ IS      1.88E-18      RS      0.9255
+ N       1            IKF     98.29122743
+ EG      1.2          XTI     3
+ CJO     7.90E-11     VJ      0.367
+ M       1.63         FC      0.5
+ TT      1.00E-10     BV      1500
+ IBV     1.00E-03     VPK     1200
+ IAVE    1            TYPE    SiC_Schottky
+ MFG     GeneSiC_Semiconductor
.MODEL GB01SHT12_PIN D
+ IS      2.76E-16      RS      0.84243
+ N       3.791461     IKF     2.98675
+ EG      3.23         XTI     30
+ FC      0.5          TT      0
+ BV      1500         IBV     1.00E-03
+ VPK     1200         IAVE    1
+ TYPE    SiC_PiN
.ENDS
*
*      End of GB01SHT12-CAL SPICE Model
```