

# AZ100LVEL58



## PECL/ECL 2:1 Multiplexer

[www.azmicrotek.com](http://www.azmicrotek.com)

### DESCRIPTION


The [AZ100LVEL58](#) is a 2:1 multiplexer. The device is pin and functionally equivalent to the AZ100EL58. With AC performance similar to the AZ100EL58 device, the LVEL58 is ideal for the low voltage applications that require the ultimate in AC performance. If desired, the select input can be directly driven from a CMOS output.

The AZ100LVEL58 is a direct replacement for the ON Semi MC100LVEL58.

### FEATURES

- 440ps propagation delay
- Operating voltage of 3.0 to 5.5V
- Internal input pull-down resistors
- Direct replacement for ON Semi MC100LVEL58

### BLOCK DIAGRAM



### APPLICATIONS

- General applications

### PACKAGE AVAILABILITY

- MLP8
- SOIC8
- MSOP8

Order Number	Package	Marking
AZ100LVEL58DG <sup>1</sup>	SOIC8	AZM100GLVEL58 <sup>2</sup>
AZ100LVEL58TG <sup>1</sup>	MSOP8	AZHGLV58 <sup>2</sup>
AZ100LVEL58N+ <sup>1</sup>	MLP8	L5+ <sup>2</sup>

<sup>1</sup> [Tape & Reel](#) - Add 'R1' at end of order number for 7in (1k parts), 'R2' (2.5k) for 13in

<sup>2</sup> See [www.azmicrotek.com](http://www.azmicrotek.com) for [date code format](#)

## PIN DESCRIPTION AND CONFIGURATION

Table 1 - Pin Description

Pin	Name	Type	Function
1	NC		
2	D0	Input	Data Input
3	D1	Input	Data Input
4	SEL	Input	Select Input
5	V <sub>EE</sub>	Power	Negative Supply
6	$\overline{Q}$	Output	Data Output
7	Q	Output	Data Output
8	V <sub>CC</sub>	Power	Positive Supply




Figure 1 - Pin Configuration for MLP8 & SOIC8/MSOP8, respectively

**ENGINEERING NOTES**

Table 2 – Functionality Table

SEL	Q
HIGH	D0
LOW	D1

**PERFORMANCE DATA**

Table 3 – Absolute Maximum Ratings

Absolute Maximum Ratings are those values beyond which device life may be impaired.

Symbol	Characteristic	Condition	Rating	Unit
V <sub>CC</sub>	PECL Power Supply	V <sub>EE</sub> = 0V	0 to +8.0	V
V <sub>I</sub>	PECL Input Voltage	V <sub>EE</sub> = 0V	0 to +6.0	V
V <sub>EE</sub>	ECL Power Supply	V <sub>CC</sub> = 0V	-8.0 to 0	V
V <sub>I</sub>	ECL Input Voltage	V <sub>CC</sub> = 0V	-6.0 to 0	V
I <sub>OUT</sub>	Output Current	Continuous	50	mA
		Surge	100	
T <sub>A</sub>	Operating Temperature Range		-40 to +85	°C
T <sub>STG</sub>	Storage Temperature Range		-65 to +150	°C
ESD <sub>HBM</sub>	Human Body Model		2500	V
ESD <sub>MM</sub>	Machine Model		200	V
ESD <sub>CDM</sub>	Charged Device Model		2500	V

Table 4 – ECL DC Characteristics

ECL DC Characteristics ( $V_{EE} = -3.0V$  to  $-5.5V$ ,  $V_{CC} = GND$ )

Symbol	Characteristic	-40 °C			0 °C			25 °C			85 °C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$V_{OH}$	Output HIGH Voltage <sup>1</sup>	-1085	-1005	-880	-1025	-955	-880	-1025	-955	-880	-1025	-955	-880	mV
$V_{OL}$	Output LOW Voltage <sup>1</sup>	-1830	-1695	-1555	-1810	-1705	-1620	-1810	-1705	-1620	-1810	-1705	-1620	mV
$V_{IH}$	Input HIGH Voltage	-1165		-880	-1165		-880	-1165		-880	-1165		-880	mV
$V_{IL}$	Input LOW Voltage	-1810		-1475	-1810		-1475	-1810		-1475	-1810		-1475	mV
$I_{IH}$	Input HIGH Current			150			150			150			150	μA
$I_{IL}$	Input LOW Current	-150			-150			-150			-150			μA
$I_{EE}$	Power Supply Current		21	28		21	28		21	28		23	30	mA

<sup>1</sup> Each output is terminated through a 50Ω resistor to  $V_{CC} -2V$ 

Table 5 - LVPECL DC Characteristics

LVPECL DC Characteristics ( $V_{EE} = GND$ ,  $V_{CC} = +3.3V$ )

Symbol	Characteristic	-40 °C			0 °C			25 °C			85 °C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$V_{OH}$	Output HIGH Voltage <sup>1</sup>	2215	2295	2420	2275	2345	2420	2275	2345	2420	2275	2345	2420	mV
$V_{OL}$	Output LOW Voltage <sup>1</sup>	1470	1605	1745	1490	1595	1680	1490	1595	1680	1490	1595	1680	mV
$V_{IH}$	Input HIGH Voltage	2135		2420	2135		2420	2135		2420	2135		2420	mV
$V_{IL}$	Input LOW Voltage	1490		1825	1490		1825	1490		1825	1490		1825	mV
$I_{IH}$	Input HIGH Current			150			150			150			150	μA
$I_{IL}$	Input LOW Current	-150			-150			-150			-150			μA
$I_{EE}$	Power Supply Current		21	28		21	28		21	28		23	30	mA

<sup>1</sup> Each output is terminated through a 50Ω resistor to  $V_{CC} -2V$ 

Table 6 - PECL DC Characteristics

PECL DC Characteristics ( $V_{EE} = GND$ ,  $V_{CC} = +5.0V$ )

Symbol	Characteristic	-40 °C			0 °C			25 °C			85 °C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$V_{OH}$	Output HIGH Voltage <sup>1</sup>	3915	3995	4120	3975	4045	4120	3975	4045	4120	3975	4045	4120	mV
$V_{OL}$	Output LOW Voltage <sup>1</sup>	3170	3305	3445	3190	3295	3380	3190	3295	3380	3190	3295	3380	mV
$V_{IH}$	Input HIGH Voltage	3835		4120	3835		4120	3835		4120	3835		4120	mV
$V_{IL}$	Input LOW Voltage	3190		3525	3190		3525	3190		3525	3190		3525	mV
$I_{IH}$	Input HIGH Current			150			150			150			150	μA
$I_{IL}$	Input LOW Current	-150			-150			-150			-150			μA
$I_{EE}$	Power Supply Current		27	33		27	33		27	33		31	37	mA



<sup>1</sup> Each output is terminated through a 50Ω resistor to  $V_{CC} -2V$

Table 7 - AC Characteristics

AC Characteristics ( $V_{EE} = -3.0V$  to  $-5.5V$ ,  $V_{CC} = GND$  or  $V_{EE} = GND$ ,  $V_{CC} = +3.0V$  to  $+5.0V$ )


Symbol	Characteristic	-40 °C			0 °C			25 °C			85 °C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$t_{PLH}/t_{PHL}$	Propagation Delay to Output - D to Q	340	435	560				350	440	570	370	450	590	ps
	SEL to Q	540	455	570				360	460	580	380	470	600	ps
$f_{max}$	Max Toggle Freq								1.5					GHz
$t_r/t_f$	Output Rise/Fall Times Q (20%-80%)	100		260	100		260	100		260	100		260	ps

**PACKAGE DIAGRAM**  
**SOIC8**  
 Green/RoHS compliant/Pb-Free  
 MSL=1




INCHES		
DIM	MIN	MAX
A	0.189	0.196
B	0.150	0.157
C	0.050 BSC	
D	0.004	0.01
E	0.054	0.068
F	0.014	0.019
G	0.010	
H	0.0075	0.0098
I	0.016	0.034



**SOIC8 (D)**




**PCB LAND PATTERN/FOOTPRINT**




**PACKAGE DIAGRAM**  
**MSOP8**  
 Green/RoHS compliant/Pb-Free  
 MSL=1



**MSOP8 (T)**




**PCB LAND PATTERN/FOOTPRINT**



DIM	INCHES	
	MIN	MAX
A	0.118±0.004	
B	0.118±0.004	
C	0.192±0.008	
D	0.0256 TYP	
E	0.004±0.002	
F	0.034±0.002	
G	0.009±0.014	
H	0.010	
I	0.006±0.002	
J	0.021±0.004	

# PACKAGE DIAGRAM

MLP8  
Green/RoHS compliant/Pb-Free  
MSL=1



Arizona Microtek, Inc. reserves the right to change circuitry and specifications at any time without prior notice. Arizona Microtek, Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Arizona Microtek, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Arizona Microtek, Inc. does not convey any license rights nor the rights of others. Arizona Microtek, Inc. products are not designed, intended or authorized for use as components in systems intended to support or sustain life, or for any other application in which the failure of the Arizona Microtek, Inc. product could create a situation where personal injury or death may occur. Should Buyer purchase or use Arizona Microtek, Inc. products for any such unintended or unauthorized application, Buyer shall indemnify and hold Arizona Microtek, Inc. and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Arizona Microtek, Inc. was negligent regarding the design or manufacture of the part.