



SPECIFICATIONS

OPERATING VOLTAGE 9–15 VDC
 OPERATING CURRENT: 120 mA typ

	100–1000 MHz	1–2 GHz	2–3 GHz
GAIN (dB min)	18	21	18
OUTPUT P1dB (dBm min)	16	15	14
OUTPUT P1dB (dBm typ)	18	17	16
NOISE FIGURE (dB max)	6	6	7
INPUT RL (dB typ)	–18	–20	–18
OUTPUT RL (dB typ)	–10	–15	–10



PASTERNAK ENTERPRISES, INC.

P.O. BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE1516

DES. SMA FEMALE LOW NOISE AMPLIFIERS

Rev. -

FSCM NO. 53919

CAD FILE 102610

SCALE N/A

SIZE A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.