

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.

TELEPHONE: (201) 376-2922
 (212) 227-6005
 FAX: (201) 376-8960

2N3644 • 2N3645 • PN3644 • PN3645

PNP SMALL SIGNAL GENERAL PURPOSE AMPLIFIERS AND SWITCHES

ABSOLUTE MAXIMUM RATINGS


| | 2N3644/45 | PN3644/45 |
|--|-------------------|-------------------|
| Maximum Temperatures | | |
| Storage Temperature | -55° C to +125° C | -55° C to +150° C |
| Operating Junction Temperature | 125° C | 150° C |
| Lead Temperature (10 seconds) | 260° C | 260° C |
| Maximum Power Dissipation (Notes 2 & 3) | | |
| Total Dissipation at 25° C Case Temperature | 0.07 W | 1.0 W |
| at 25° C Ambient Temperature | 0.3 W | 0.625 W |
| Maximum Voltages and Current | 2N/PN3645 | 2N/PN3644 |
| V _{CB0} Collector to Base Voltage | -60 V | -45 V |
| V _{CEO} Collector to Emitter Voltage (Note 4) | -60 V | -45 V |
| V _{EB0} Emitter to Base Voltage | -5.0 V | -5.0 V |
| I _C Collector Current | 500 mA | 500 mA |

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted)


| SYMBOL | CHARACTERISTIC | 2N3644 PN3644 | | 2N3645 PN3645 | | UNITS | TEST CONDITIONS |
|-----------------------|---|------------------|------|------------------|------|-------|---|
| | | MIN. | MAX. | MIN. | MAX. | | |
| h _{FE} | DC Current Gain | 40 | | 40 | | | I _C = 100 μA, V _{CE} = -10 V |
| h _{FE} | DC Pulse Current Gain | 80 | | 80 | | | I _C = 1.0 mA, V _{CE} = -10 V |
| | | 100 | | 100 | | | I _C = 10 mA, V _{CE} = -10 V |
| | | 80 | 240 | 80 | 240 | | I _C = 50 mA, V _{CE} = 1.0 V |
| | | 100 | 300 | 100 | 300 | | I _C = 150 mA, V _{CE} = -10 V |
| | | 20 | | 20 | | | I _C = 300 mA, V _{CE} = -2.0 V |
| h _{fe} | High Frequency Current Gain | 2.0 | | 2.0 | | | I _C = 20 mA, V _{CE} = -20 V, f = 100 MHz |
| C _{ob} | Output Capacitance | | 8.0 | | 8.0 | pF | I _E = 0, V _{CB} = -10 V, f = 140 kHz |
| C _{ib} | Input Capacitance | | 35 | | 35 | pF | I _C = 0, V _{EB} = -0.5 V, f = 140 kHz |
| V _{CE(sat)} | Pulsed Collector Saturation Voltage | -0.25 | | -0.25 | | V | I _C = 50 mA, I _B = 2.5 mA |
| | | -0.4 | | -0.4 | | V | I _C = 150 mA, I _B = 15 mA |
| | | -1.0 | | -1.0 | | V | I _C = 300 mA, I _B = 30 mA |
| V _{CEO(sus)} | Collector to Emitter Sustaining Voltage | -45 | | -60 | | V | I _C = 10 mA (pulsed), I _B = 0 |
| V _{BE(sat)} | Pulsed Base | -1.0 | | -1.0 | | V | I _C = 50 mA, I _B = 2.5 mA |
| | | -1.3 | | -1.3 | | V | I _C = 150 mA, I _B = 15 mA |
| | | -0.8 | -2.0 | -0.8 | -2.0 | V | I _C = 300 mA, I _B = 30 mA |
| BV _{EBO} | Emitter to Base Breakdown Voltage | -5.0 | | -5.0 | | V | I _C = 0, I _E = 10 μA |
| BV _{CB0} | Collector to Base Breakdown Voltage | -45 | | -60 | | V | I _C = 100 μA, I _E = 0 |
| t _{on} | Turn On Time | | 40 | | 40 | ns | I _C ≈ 300 mA, I _{B1} ≈ 30 mA, V _{CC} = -30 V |
| t _{off} | Turn Off Time | | 100 | | 100 | ns | I _C ≈ 300 mA, I _{B1} ≈ I _{B2} ≈ 30 mA, V _{CE} = -30 V |
| I _{CES} | Collector Reverse Current | | 35 | | 35 | nA | V _{CE} = -30 V, V _{BE} = 0 |
| | | | 2.0 | | 2.0 | μA | V _{CE} = -50 V, V _{BE} = 0 |
| | | | | | | μA | V _{CE} = -30 V, V _{BE} = 0, T _A = 65° C |
| | | | | | | μA | V _{CE} = -50 V, V _{BE} = 0, T _A = 65° C |

TO-92

PN3644
 PN3645



TO-105



2N3644
 2N3645

SEATING PLANE
 MILLIMETER DIMENSIONS ARE GIVEN FROM BASE UNLESS OTHERWISE NOTED

| SYMBOL | INCHES | | MILLIMETERS | | TOLERANCE |
|--------|--------|------|-------------|------|-----------|
| | MIN. | MAX. | MIN. | MAX. | |
| A | .122 | .200 | 3.1 | 5.0 | |
| B | .190 | .210 | 4.83 | 5.33 | |
| C | .016 | .021 | .407 | .533 | ±.002 |
| D | .016 | .019 | .407 | .483 | ±.002 |
| E | .200 | .225 | 5.08 | 5.71 | |
| F | .080 | .110 | 2.28 | 2.79 | |
| G | .500 | .. | 12.70 | .. | ±.005 |
| H | .. | .000 | .. | 0.00 | ±.002 |
| I | .150 | .. | 3.81 | .. | ±.005 |
| J | .080 | .. | 2.03 | .. | ±.005 |
| K | .125 | .. | 3.18 | .. | ±.005 |



Quality Semi-Conductors