



157DER2R5SCP

Radial lead, +70°C

Parts are RoHS compliant

ELECTRICAL SPECIFICATIONS

Capacitance: 150 F

Temperature Range: -25°C to +70°C

ESR (AC): 22 milliOhms Max at 20°C and 1 kHz

ESR (DC): 30 milliOhms Max at 20°C and DC

Tolerance: -20 % , +50 %

WVDC: 2.5 Volts DC

SVDC: 2.7 Volts DC

Weight: 33.8 grams

Maximum stored energy: 130.207 Watt hours

Volume: 26.998 ml

Maximum Current: 34.1 Amps (1 second discharge to 1/2 the rated voltage)

Operating Current: 37.5 Amps (5 sec discharge to 1/2 rated voltage)

Leakage Current: 0.55 mA after 72 hours

Specific Energy:

Specific Power:

Gravimetric Density: 3.8523 Wh/kg

Volumetric Density: 4.8229 Wh/l

Gravimetric Density: 0.7396 kW/kg

Volumetric Density: 0.926 kW/l

Load Life: 1000 hours at 70°C with 100% of rated voltage applied

Max Capacitance Change: ≤30% of initially measured value

ESR Change: ≤200% of maximum specified value

PHYSICAL DIMENSIONS

Diameter (D): 25 mm, +/- 0.5 mm

Length (L): 55 mm, +/- 1.5 mm

Height (H): mm, +/- mm

Thickness (T): mm, +/- mm

Termination Finish: Matte Tin

Lead Spacing (S): 10 mm, +/-0.5 mm

Lead Diameter (d): mm, +/- mm

Lead Length (LL): 4mm, +/- 1 mm

