

# Isc N-Channel MOSFET Transistor

# STP60N06-14

**• FEATURES**

- With low gate drive requirements
- Easy to drive
- High current capability
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**• APPLICATIONS**



- Solenoid and relay drivers
- DC-DC converters
- Automotive environment

**• ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)**

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>DSS</sub>	Drain-Source Voltage	60	V
V <sub>GSS</sub>	Gate-Source Voltage	±20	V
I <sub>D</sub>	Drain Current-Continuous@T <sub>c</sub> =25°C T <sub>c</sub> =100°C	60 50	A
I <sub>DM</sub>	Drain Current-Single Pulsed	240	A
P <sub>D</sub>	Total Dissipation	150	W
T <sub>j</sub>	Operating Junction Temperature	-65~175	°C
T <sub>stg</sub>	Storage Temperature	-65~175	°C

**• THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
R <sub>th(ch-c)</sub>	Channel-to-case thermal resistance	1.0	°C/W
R <sub>th(ch-a)</sub>	Channel-to-ambient thermal resistance	62.5	°C/W



**Isc N-Channel MOSFET Transistor**

**STP60N06-14**

**ELECTRICAL CHARACTERISTICS**

T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V; I <sub>D</sub> = 0.25mA	60			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =±20V; I <sub>D</sub> =0.25mA	1			V
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> = 10V; I <sub>D</sub> =30A		12	14	mΩ
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> = ±20V; V <sub>DS</sub> = 0V			±0.1	μA
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> = 60V; V <sub>GS</sub> = 0V; T <sub>J</sub> =25°C V <sub>DS</sub> = 48V; V <sub>GS</sub> = 0V; T <sub>J</sub> =125°C			250 1000	μA
V <sub>SDF</sub>	Diode forward voltage	I <sub>SD</sub> =60A, V <sub>GS</sub> = 0 V			1.6	V